



WATER DRAFTING SPECIFICATIONS

National Marine Fish Service
Southwest Region

August 2001

“Water-drafting” is a short-duration, small-pump operation that withdraws water from streams or impoundments to fill conventional tank trucks or trailers. Usually, this water is used to control road dust, or for wildfire management.¹ Short term water drafting is also used to temporarily de-water a construction site, or to temporarily divert water around a construction site.

The specifications below are given primarily for the protection of juvenile anadromous salmonids, in waters where they are known to exist; but they also may be applied to protect a host of other aquatic organisms as well. The issue of sufficient in-stream flow for life support of the aquatic ecosystem should be addressed by a local Fish & Game biologist. Temporal and cumulative effects should be considered on a watershed scale. While we give some guidelines in that area, the actual impact of water drafting on stream ecology should be assessed and monitored at the local level by qualified personnel.

The main focus of this guidance is the construction, operation, and maintenance of a fish screen module(s) that must be installed at the in-stream end of the drafting hose to protect small salmon and steelhead fry from being entrained in the hose, or impinged on the surface of the screen. The specifications are based on the critical “approach velocity” at the screen surface², and a recognition that many temporary screens will not be outfitted with automatic cleaning devices to remove debris buildup. Since it is difficult to measure water velocities in the field, only the construction, pumping capacities, and operations are specified. Variances from these specifications may be considered on a case-by-case basis.

¹ In case of emergency wildfire, where human life is in danger, the operator may disregard the screening requirement if a suitable screen is not immediately accessible.

² Approach velocity is the horizontal velocity vector component, typically measured at a distance of 3 inches from the screen face.

Operating Guidelines

1. Operations are restricted to one hour after sunrise to one hour before sunset.³
2. Pumping rate shall not exceed 350 gallons per minute.
3. The pumping rate shall not exceed ten percent of the stream flow.⁴
4. Seek streams and pools where water is deep and flowing, as opposed to streams with low flow and small isolated pools.
5. Pumping shall be terminated when the tank is full. The effect of single pumping operations, or multiple pumping operations at the same location, shall not result in obvious draw-down of either upstream or downstream pools.
6. Each pumping operation shall use a fish screen. The screen face should be oriented parallel to flow for best screening performance. The screen shall be designed and used such that it can be submerged with at least one-screen-height-clearance above and below the screen.
7. Operators shall keep a log on the truck containing the following information: *Operator's Name, Date, Time, Pump Rate, Filling Time, Screen Cleaned (Y or N), Screen Condition, Comments*. These guidelines should be included as instructions in a logbook with serially numbered pages. This assures each truck operator easy access to this information.

Screen Construction Criteria

1. Surface Area

The total (unobstructed) surface area of the screen shall be at least 2.5 square feet, based on the upper limit of pumping of 350 gpm⁵. Larger surface areas are recommended where debris buildup is anticipated, and where stream depth is adequate to keep the screen submerged at approximately mid-depth.

2. Screen Mesh

Screen Mesh must be in good repair and present a sealed, positive barrier- effectively preventing entry of the "design fish" into the intake. The design fish in this case is a immature (20-30mm) salmon or steelhead fry.

The screen mesh size shall be:

- Round openings - maximum 3/32 inch diameter (.09 inch)
- Square openings - maximum 3/32 inch diagonal (.09 inch)
- Slotted openings - maximum 1/16 inch width (.07 inch)

3. Screen Design

Water drafting screens may be off-the-shelf products, but they are often custom-made devices

³ Restricting operations to daylight-only prevents the use of lights that will attract fish to the drafting pool

⁴ Restricting drafting to ten percent of the stream flow provides adequate downstream flow to support fish, aquatic insects, amphibians, and other biota. Ten percent of flow may be estimated by pump operators.

⁵ If larger pumping volumes are needed, or if the pumping application is continuous, refer to <http://swr.nmfs.noaa.gov/habitat.htm> and review addendum for small pump intakes.

appropriate to the scale and duration of pumping operation. To keep the screen supported and correctly positioned in the water column, adjustable support legs are advised. Screen geometry can be configured either as rectangular or cylindrical, i.e.- as a shallow “box-shape” or tubular.

The intake structure shall be designed to promote uniform velocity distribution at all external mesh surfaces. This can be accomplished with a simple internal baffle device that distributes the flow evenly across the entire surface of the screen. In order to accomplish this, the designer needs to understand the hydraulic characteristics of these devices. There is a tendency for most of the intake water to enter the screen near the hose end, so a typical internal baffle would consist of a pipe (or a manifolded set of pipes) which have variable porosity holes at predetermined spacing. We recommend starting near the hose end with approximately 5-10% average open area, and gradually increasing the porosity toward the length of the screen. At a point where screen length exceeds three times the diameter of the suction hose, the baffling effect tends to diminish rapidly. At this point the baffle porosity may approach 100%. A successful baffle system will functionally distribute flow to all areas of the screen. A poorly designed screen may result in high-velocity “hot spots,” which could lead to fish impingement on the screen face. Hydraulic testing of prototype screen designs is recommended where the application is on-going and extensive.

4. Screen Structure

The screen frame must be strong enough to withstand the hydraulic forces it will experience. However, structural frames, braces, and other elements that block the flow, change flow direction, or otherwise decrease the screen surface area should be minimized.

5. Screen Cleaning

The screen shall be cleaned as often as necessary to prevent approach velocity from exceeding 0.33 feet per second. Operators should withdraw the screen and clean it after each use, or as necessary to keep screen face free of debris. Pumping should stop for screen cleaning when approximately fifteen percent or more of the screen area is occluded by debris. A suitable brush shall be on board the truck for this cleaning operation.

If the operator notes (a) impingement of any juvenile fish on the screen face or (b) entrainment of any fish through the screen mesh, he/she should stop operations and notify the Department of Fish & Game and/or NMFS hydraulic engineering staff :

National Marine Fisheries Service
Engineering Section
777 Sonoma Avenue, Suite 325
Santa Rosa, CA. 95404
(707) 575-6050

Rebecca Lent, Ph.D.
Regional Administrator