REPEALED

SHORELINE PROTECTION TABLES (SP TABLES) FOR VESSEL TRAFFIC IN CALIFORNIA'S MARINE WATERS (Tables Dated August 29, 2013)

PURPOSE AND SCOPE

The Shoreline Protection Tables (SP Tables) set forth planning requirements for shoreline protection for vessels in California's marine waters. A vessel owner/operator shall demonstrate through contracts(s) or other approved means (see Sections 815.05(b) or 825.05(a)), the shoreline protection response resources necessary to protect each type of shoreline and all applicable sensitive sites as outlined in the appropriate SP Tables. Based on these Tables the owner/operators will be able to ascertain the type of equipment that must be available for the appropriate response strategies necessary to protect the shoreline types that could be affected. For the purpose of meeting the regulatory requirements, contracts for shoreline protection services can only be made with OSROs Rated by the Office of Spill Prevention and Response.

The SP Tables are for vessels that transit in California's marine waters. In addition, for the small harbors identified, a Small Harbor Table is included to define preparedness levels for these areas.

The requirements set forth in these Tables are planning standards and may not reflect the exigencies of actual spill response. However, these are the standards that must be used to determine the amount of equipment and personnel that must be under contract or other approved means. The owner/operator is ultimately responsible for protecting the sensitive sites identified from the entire volume of an actual spill regardless of the planning volume.

Skimming assets required to execute the strategies listed in the Tables will be included as part of the required on-water recovery capacity, as stipulated in CCR Sections 818.02(e) and 827.02(h), and should not be construed as requiring additional skimming capacity. Sorbent boom requirements included in the first 24 hours of response must be on scene by hour 24, but not necessarily deployed at specific sites. In a few instances (only as indicated in the Tables) up to 2,000 feet of containment boom required to meet the 2-hour on-water containment requirement, can be utilized for shoreline protection.

An owner/operator may propose alternatives to what is listed in the SP Tables for boats and staff only. The proposal may be tested by the Administrator anytime prior or subsequent to plan approval. The SP Tables shall be reviewed and updated as needed (e.g., to reflect updates to the ACPs, etc.). Updates to the SP Tables will be processed by OSPR staff using the procedures outlined in the Administrative Procedure Act.

A glossary of terms used in the SP Tables has been included (last page). This glossary explains the terms and abbreviations used in the tables. These are the commonly understood meanings of these terms, and are included here to make the SP Tables comprehensive, stand-alone documents.

To the greatest extent possible, California has endeavored to be consistent with the scope and intent of the Federal oil spill response regulations and the Area Contingency Plans (ACP) completed by the U.S. Coast Guard, state agencies, and local governments, with public participation, as required by the Oil Pollution Act of 1990 (33 USC 2701, et seq.).

Site Name First 6 hours Palko Marsh Paleo Marsh Paleo Marsh Indian Isl (swamp boom supports 1-310.2 strategy)	Harber Swar Beem 2000		Boom Sorbent Type Boom	Anchoring Systems No. Kind 15	Boom Boats	Skiffs N	kimmers	Special Equipment and Notes	
First 6 hours Palko Marsh Palco Marsh Palco Marsh	Boom		Type Boom	No. Kind	Boats	Skiffs N	_	0 110 1 1 111	
Palko Marsis Paleo Marsis Paleo Marsis	2400	4000 0	1	15			o. Type	Special Equipment and Notes	Ste
Paleo Marsh Paleo Marsh									
Paleo Marsh Paleo Marsh								Flash boards & keys to tide gates at Cheyron & city	
								debris hooks, shovels, pry bar, pitchfork	
Indian Isl (swamp boom supports 1 310.2 strategy)			1					,,,,,,	
		500		22 lb+ Danforth anchors	4				
Elk River & Marshes		_						Close drop gates bolt cutters or keys for lock	
								cross drop gates - bott cutters of acys for rock	
,,		3500		5 22 lb+ Danforth anchors	2		1-SPS		J
			<u> </u>	1	I				
		0	30						
					+		1-SPS		
	1400		30	5 22 lb+ Danforth anchors		1			
Elk River & Marshes							1-SPS/SSS		
13 24 hours	750	400 0	155). 123					
Woodley Island	1200	-		4 22 lb+ Danforth anchors	1		1-SPS	Stakes.shovels. hammer	
South Humboldt Bay	1200			5 22 lb+ Danforth anchors	2		2 SSS	, ,	
Eureka Slough		1000	10		4		1-SSS	collection and containment package	
North Humboldt Bay	2000			10 22 lb+ Danforth anchors	4		1-SFS		
Mad River Slough	1200	100	120	4 22 lb+ Danforth anchors					
Arcata Ray Slaughe - Jacoby Creek	500	100	10					Stakes should hammer	
		100							
			10						
Arcata Bay Sloughs McDonald Slough								Stakes shovels, hammer	
	7-12-hours Humboldt Bay Mouth / Samoa Spit Woodleylsland Elik River & Marshes Elik River & Marshes 13-24-hours Woodley Island South Humboldt Bay Eureka Slough North Humboldt Bay Mad River Slough Areata Bay Sloughs—Jacoby Creek Areata Bay Sloughs—Gannon Slough Areata Bay Sloughs—Gannon Slough	Int boom required to meet the 2-hour on water containment requirement can be utilized 7-12-hours 4600 Humboldt Bay Mouth / Samoe Spit 2000 Woodley-island Elk River & Marshes Lik River & Marshes 1400 Elk River & Marshes 1400 Suth Humboldt Bay Livel Stough North Humboldt Bay Livels Stough North Humboldt Bay Areata Bay Stoughs - Jacoby Creek Areata Bay Stoughs - Gannon Stough 500 Areata Bay Stoughs - Gannon Stough	Introduction International Internation Internation Internation Internation Internation International Internation Internation Internation Internation Internation International Internation International Intern	Introduction Interview I	Note Note	December December	North Humboldt Bay North H	Note Part Part	Action Page Page

SHORELINE PROTECTION TABLE - CALIFORNIA NORTH COAST - PT ARENA 8/2013

Special Equipment and Notes

Other Boom Amt Type

		First 6 hours	600	300	0	0	3			0		10
2	1-484.3	Garcia River & Manchester State Beach	600				3 22 lb+ Danforth anchors		1			5
2	1-486.1	Point Arena	on water respon	se only; no shore	line protection feasible							
5	1-482.2	Alder Creek		300								5
		7 to 24 hours	1400	•	100	300	28			0		
13	1 474.2	Greenwood Creek to Cuffey's Cove									over flight assessment needed	19
13	1-476.1	Bonee Gulch	on-water respons	se only; no shore	line protection feasible							
13	1 478.1	Elk Creek	on water respon	se only; no shore	line protection feasible							
16	1-472.2	Navarro River St Pk	1000				12 22 lb+ Danforth anchors		2			8
17	1-470.1	Salmon Point and Big Salmon Creek							Ţ		install filter fence: fencing & 200 pom poms	3
18		Albion River	300			300	12 22 lb+ Danforth anchors		1			5
24	1 464.2	Van Dam St Pk and Little River	100		100 OS		4 22 lb+ Danforth anchors	-				3

by hour	Strategy or Site Number	Site Name	H arbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boats	Skiffs	Skimmers No. Type	Special Equipment and Notes	
<i>,</i>		First 6 hours	3000	boom (50 50		15-20	Douts	DRITIS	8	Special Equipment and votes	
,	2-201.1	Pt. Reyes Headlands	on water respons	e only; no shore	line protection feasible							
,	2-203.2	Drakes Beach (West)	3000		50 OS	100	15-20-22#+ Danforth	34			Storage tanks, bladders or vac trucks	
,	2-207.1	Limnatour Spit									Front end loadergader	
		7-24 hours	6000	5080	3100	8900	96					
3	2-198.1	Point Reyes Beach	on-water res	ponse only; no	shoreline protection feasible							,
2	2 205.1	Drakes Estero			2000 OB*		25 40#+ Danforth	4				
2	2-205.2	Drakes Estere	6000		50 OS	2100	30 22#+ Danforth	4	4			
2	2-210.1	Point Resistance	on-water respons	e only; no shore	line protection feasible							
2	2-213.1	Miller Point	on-water respons	e only; no shore	line protection feasible							
2	2-216.2	Double Point and Stormy Stack			1000 OB*		10 40#+ Danforth	2				
12	2 219.12	Duxbury Reef				5000						
4	2-198.1	Pt. Reyes Beach	on-water respons	e only; no shore	line protection feasible							
8	2 -197.2	Abbott's Lagoon (if not naturally closed)		500		600	4 12#+ Danforth		+			<u> </u>
9	2 222.1	Bolinas Lagoon		4380	50 OS	200	25 15x22#, 10x30 45#, 8 stakes		3			
24	2-225.1	Redwood Creek/Big Lagoon/Muir Beach		200		1000	2 small anchors or stakes					
4	2-231.1	Bird Island	on-water respons	e only; no shore	line protection feasible							
<u> </u>	>=: INI	E PROTECTION TABL	F 0 F 00		COASTA		LAR PT.	8/2013				

		First 6 hours	0	- 50	9	54	98					2
2	2-260.1	Seal Cove to Pillar Point	on water respons	se only; no shore	line protection feasible							
5	2-255.1	Shelter Cove & San Pedro Rock	on water respons	se only; no shore	line protection feasible							
5	2-258.1	Point Montara Area	on-water res	ponse only; no	shoreline protection feasible							
6	2-253.1	San Pedro Creek		54)	5	8 stakes					2
		7-24 hours	500	12350	a	20	25)			1		19
11	2-264.4	Pillar Point Marsh & Denniston Creek	500				9 2/50+ & 7/22 danforths + 20' chain	1	1	1 vessel sk		5
12	2-264.1	Pillar Point Marsh & Denniston Creek						·			culverted berm using sandbags or earthmovers	2
12	2-264.2	Pillar Point Marsh & Denniston Creek		5()		3 stakes				stake to keep from catinary sag.	2
16	2-264.5	Pillar Point Marsh & Denniston Creek		12300)	20	13 12+# danforths & stakes	2	2			10

SHO	RELINE	PROTECTION TABLE - S	.F. SE	СТОГ	R - SOUTI	H S.F.	BAY / ANCHORAGE 9			8/2013		
Protect by hour	Strategy or Site Number	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boats	Skiffs	Skimmers No. Type	Special Equipment and Notes	Staff
		First 6 hours	8800	300	0	900	23			0		39
2	2-307.1	Alameda Eelgrass Beds									Initial on site assessment needed	1
3	2-304.1	Middle Harbor Shoreline Park	2500				7 7/22 + danforth	2	1			7
3	2-309.1	San Leandro Bay	1200	300		200	5 22+# danforth & chain	2	1		Bboat: very shallow draft	8
3	2-351.1	Yerba Buena Island	3000				7 22+# w/ 20' 1/2" chain	3	1		3000' 1/2" anchor line	11
4	2-309.2	SanLeandre Bay	1500				4 22+# danforth	2	1			8
4	2-310.1	Bay Farm Island Eelgrass Beds									Initial on site assessment needed	
6	2-401.1	Pier 39	1600			700	tie boom to pilings/breakwall	4			boom tending for traffie	3
		7 12 hours	2000	550	0	250				0		8
12	2-353.1	Heron's Head Park India Basin		200		200	12 12 stakes					2
12	2-354.1	Islais Creek Pier 94 Saltmarsh	1000	50		50	3 22+# danforths & stakes	4	1			3
12	2-403.1	Crissy Field Tidal Marsh		300			12+/danforth w chain & 2 stakes		1			3
12 2-415	.l Horse	hoe Bay	1000			- 3	3/22# danforth		1	1 vac	-truck	
		13 18 hours	8000	1950	0	600	29					29
14	2-312.1	Oyste PointBay		850			6 12#+ danforths + 4 stakes		2			4
14	2-352.2	South Basin, Hunters Point	500				2 22+# danforth	4			shallow water Bboat	3
18	2 454.1	Richmond Inner Harbor/Hoffman Marsh	2500	1100		200	6 - 8 22+# danforth, 15' 1/2 chain	2	2	1	Shallow draft boom boat.	8
18	2-480.2	Albany Marsh	1700			100	9 22+# danforth	2	į.	1 Shallow	very shallow Bboats , skimmers & stakes.	8
24	2-420.2	Richardson Bay Marshes	3300			300	6 22+# danforths + chain	2				6

SHO	RELINE	PROTECTION TABLE - S	.F. SE	СТО	R - CENTF	RAL S	AN FRANCISCO BAY			8/2013		
Protect by hour	Strategy or Sit Number	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boats		Skimmers No. Type	Special Equipment and Notes	Staff
		First 6 hours	12900	0	0		936			0		45
3	2 304.1	Middle Harbor Shoreline Park	2500				7 7/22 + Danforth	2	1	SSS		7
3	2-351.1	Yerba Buena Island	3000				7 22#+ w/ 20' 1/2" chain	3	1		3000' 1/2" anchor line	11
5	2-453.1	Brook's Island	2300				7 22+# danforths + chain	4	1		boom boat capable of withstanding grounding	4
5	2 495.1	Emeryville Lagoon/Mudflats	3600				7 22#+ danforth + 15' chain	3	2		Bboat: I very shallow draft	11
5	2-490.1	Berkeley Eelgrass Beds									Initial on-site assessment needed	1

6	2 480.1	Albany Marsh	1500				8 <u>22#+ danforths</u>	2	2		very shallow Bboats , skimmers & stakes.	#
		7-12 hours	3500	2500	4050	3300	36					40
7	2-454.1	Richmond Inner Harbor/Hoffman Marsh	2500	1100		200	8 22#+ danforth, 15' 1/2 chain	2	2	+	Shallow draft boom boat.	8
9	2-234.2	Point Bonita and Bonita Cove			2000 OB*		10 40 60# Danforth	2				9
9	2-236.2	Pt. Diablo to Lime Point			2000 OB*		8-10 40-60# Danforth	2				13
9	2-415.1	Horseshoe Bay	1000				3 3/22# Danforth		1		I vac Truck	2
#	2-225.1	Redwood Creek/Big Lagoon/Muir Beach		200		1000	2 small anchors or stakes					2
#	2-228.1	Rodeo Lagoon		1200	50 OS	2100	6 small anchors or stakes		1-2			6
		13 18 hours	8300	250	0	1550	25			0		31
13	2 401.1	Pier 39	1600			700	tie boom to piling s/breakwal l	1			boom tending for traffic	3
13	2-451.1	Castro Rocks	3000			300	10 5/40+ northhill & 7/22+ danforth	3			maneuverable Bboats & 1500' line	11
14	2-420.1	R i ch ardson ByMarshes	2700			300	12 22+# danforths + chain	3	1		Bboats capable of shallows & obstructions	11
14	2-506.1	San Pablo Bay EejgrassBed									Initial on-site assessment needed	1
15	2-353.1	Heron's Head Park - India Basin		200		200	12 stakes	ļ				2
15	2-354.1	Islais Creek - Pier 94 Saltmarsh	1000	50		50	3 22#+/danforths & stakes	Į.	1			3
		19-24 hours	1500		0	0	4					

SHORELINE PROTECTION TABLE - S.F. SECTOR - SAN PABLO BAY GRA 5 8/2013

	Strategy or Site											
Protect by hour	Number	Site Name	Harbor Boom	Swamp	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boats		Skimmers	Consider Considerate and Material	24-42
Protect by nour		Site Name	Boom	Boom	Amt Type	Boom	No. King	Boats	SKITIS	No. Type	Special Equipment and Notes	Staff
		First 6 hours	8500	1200	0	900	11			4		35
3	2-452.2	Richmond Eelgrass Beds	2500				6 22#+chain	2	1			6
4	2-501.1	Castro Creek and Marshes	4000				10 22#+/Danforth + 20' chain	4				12
4	2-502.1	San Pablo Creek Marshes	2000				15 12+# Danforth	2	2			10
4	2-506.1	San Pablo Bay Eelgrass Bed									Initial on site assessment needed.	
5	2-503.1	Pinole Pt. Marshes South		900		900	8 12#+ Danforth anchors	1	1			5
6	2.452.1	Richmond Eelgrass Beds		300			2 stakes or anchors	0	1			2
		7-12 hours	8400	4900	0	6000	38			0		25
7	2 451.3	Castro Rocks	3000	2500			15 5/40#+ northhills & 10/22#+Danforths	3			maneuverable Bboats & 1500 line	#
7	2-503.2	Pinole Pt. Marshes South	5400			6000	16 22#+ danforth	2	1			8
10	2-422.1	Keil Cove		2400			7 20#+ w 10' 1/2" chain	2			1,200 feet ofM/2"ancho rofe	6
		13-24 hours	9000	3200	0		24			0		24
13	2-451.2	Castro Rocks (flood tide, oil from S or SE)	6000				9 5/40 # Danforth and 4/22 # Danforth	3	1		maneuverable Bboats & 1500' line	11
16	2-453.2	Brook's Island		3200			8 5/22 #+/danforth & 3-stakes	1	1		boom boat capable of withstanding grounding	4
24	2-427.1	Marin Islands	3000				7-22+/danforths + chain.	3				9

SHORELINE PROTECTION TABLE - S.F. SECTOR - SUISUN BAY GRA 6 8/2013

	Strategy or Site Number	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Boom Boats		Skimmers No. Type	Special Equipment and Motae	Staff
Protect by nour		First-6-hours	9500	3450	••	5100	Dodis	OKIIIS	0	оросы сарариян ам чого	56

2	2-605.2	Hastings Slough & Point Edith Marshes	2400				6 5/22#+/danforths + 20'chain	3				9
3	2-605.1	Hastings Slough & Point Edith Marshes	1500	1100		2300	38 5/22#+ & 11/12#+ danforth & 22 stakes	2	6		bboat: shallow, strandable. Stakes	18
3	2-607.1	Weapons Station Marshes & Seal Islands		1050		900	14 4/12#+/danforth & 10 stakes		1			2
4	2-603.1	Bulls Head marsh and Pacheco Creek	1100	400		1000	4/22#+ & 5/12#+ danforths & 10 stakes	1	2		bboat: strandable, shallow water, stakes	7
4	2-631.2	Roe Island	3000				7.75#+ danforth + heavy chain	3	1			9
5	2-608.1	Shore Acres Marsh		900		900	16 3#+ danforths & stakes	1	1			3
5	2-633.1	Middle Ground Island	1500				4 22#+ danforths & chain	2	1			8
		7-12 hours	5500	5650		6500 i	.05			0		48
7	2-702.1	Stake Point Marshes	2000			600	22 4/22#+ & 6/12#+/danforths stakes &	32	2			10
7	2-752.1	Chips Island, Southern Side	300	1200		300	30 30/12+# danforths and stakes	2	1		Bboat: shallow draft	8
8	2 -601.2	Martinez Marsh	600				1 22#+/danforth + 20' chain	1				3
8	2-673.1	Honker Bay East - Chipps Island Shore	400	1700		1000	15 3/22#+ & 4/12#+& danforth & 8 stakes	2				5
9	2-601.1	Martinez Marsh		250		1300	12#+ anchor & stakes		4		boat capable of shallow grounding	2
#	2-632.1	Ryer Island	2200	1900		3000	30 15/22#+& 15/5#+/danforth 20 stakes	4	3		1 very shallow draft boats & 18 flags	18
12	2 631.1	Roe Island		600		300	6 12#+/danforths & stakes		1		very shallow boat, draft airboat or hovercraft &	2
		13-18 hours	9000	3450	0	400	59			0		65
13	2-667.1	Freeman & Snagjslands	1200	250			8 12#+/danforths & stakes	1	2			7
	2-705.1	Mallard Island	2200			400	12 825# & 4/15# danforth	3	2			14
14	2-667.2	Freeman & Snag Islands	1300				6 22#+/danforths & stakes	2				6

			SHORELINE	PRO	TECT	ION TABL	E - S.	F. SECTOR - SUISUN B	AY (GRA	6, continu	ed 8/2013	
Protec	t by hour	Strategy or Site Number	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boats		Skimmers No. Type	Special Equipment and Notes	Staff
	14	2 671.1	Honker Bay West - Wheeler Island Shore	1300	700			6 6/12#+/danforths & stakes	2	4			15
	17	2-688.1	Dutton Island		2500			22					12
	18	2.755.1	Spoonbill Creek	3000				5 22#+ danforth, 100' line, 30' chain	3	1			#
			18 24 hours EBB	19800	300	•	300	4 7			4		66
	19	2 660.1	Grizzly Bay	13000				26 22#+/danforth & chain	1-12	2		shallow draft boom boat grounding capable	40
	20	2-672.1	Honker Bay North Van Sickle Island	800	300		300	§ 12#+ danforths	2	2	1 SSS		10
	20	2.712.1	Winter Island	6000				13 22+#/danforth anchors	4	2			16

		SHORELIN	E PR	OTEC	TION TAB	LE - S	S.F. SECTOR - MONTER	REY /	NC	HORAGE /	\ 8/2013	
Protect by hour	Strategy or Site Number	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	Sorbent Boom	8 7	Boom Boats	Skiffs	Skimmers No. Type	Special Equipment and Notes	Staff
		First 6 hours	5400	0	0	0	10					12
2	3 360.1	Monterey State Beach	on water respon	se only; no shore	ine protection feasible							

2	3-370.1	Monterey Harbor Entrance	2400				7	large Danforth, as needed	2			2 mooring weights with buoys	6
2	3-375.1	USCG Jetty in Monterey Bay	3000				3	large Danforth, as needed	2				6
4	3-330.1	Monterey BayDunes	on water respons	e only; no shore	line protection feasible								
5	3-380.1	Point Cabrille	on water respons	se only; no shore	line protection feasible								
		7 - 18 hours	0	2000	0	0	8				4		10
10	3-345.1	Marina St. Beach	on-water respons	e only;	no shoreline protection	feasible		1					
16	3 340.2	Salinas River Inlet		2000			8	4 Stakes & 4 Danforths					10
17	3-325.1	Salinas River State Beach	on-water respons	se only; no shore	line protection feasible			1					
		19-24 hours	3000	1600		4200	19						10
19	3-305.1	Moss Landing inlet	3000	1600	OS*	3000	13		1	1		Anchor posts or stakes	5
19	3-310.1	EkhomSlough			OS*	1200	6		1	1		Anchor posts or stakes	5
23	3-301.1	Zmudowski Beach St. Park	on water respons	e only; no shore	line protection feasible						, and the second		

		SHORELINE PR	OTEC	TION	TABLE -	CENT	RAL COAST - PT BUCH	ION	/ MO	RRO BAY	AREA 8/2013	
Protect by hour	Strategy or Site Number	Site Name	Harbor Boon	Swamp Boom	Other Boom Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boots	Skiffs	Skimmers No. Type	Special Equipment and Notes	Staff
		First 6 hours	8700	1000	0	5100	18					56
2	4-310.2	;sayCreek		100			2 small anchors or stakes			1-SSS		4
2	4-315.1	Lion Rock	on water respon	se only; no shore	line protection feasible							
3	4-300.1	Morro Bay Sand Spit	on water respon	se only; no shore	line protection feasible							
4	4-150.1	Morro Rock	on-water respon	se only; no shore	line protection feasible							
4	4-200.1	Morro Bay julet	2000)			2 40 lb. Anchors	2		1-SFS/SPS		6
4	4-200.2	Morro Bay inlet	2000)			2 40 lb. Anchors	2		1-SSS/SPS		6
4	4-200.3	Morro Bay jnlet	3500)			2 40 lb. Anchors	2		1 SFS/SPS		6
5	4-215.1	Morro Bay St. Park Marina	1200)			2 40 lb. Anchors		2	1 SFS	fence posts	6
5	4-220.1	Morro Bay Marsh Habitat				5000			2	1-SFS	fence posts	6
5	4-225.1	Chorro Creek jnlet				54)			1-SSS	fence posts	4
5	4 -230.1	Los Osos Creek jnlet				51				1 SSS	metal stakes	4
5	4-235.2	Sweet Springs Marsh		50 300			2 small anchors or stakes			1-SSS	fence posts	4
5	4-240.1	Cuesta by the Sea julet		200			2			1-SSS		4
6	4-130.1	Morro Strand State Beach North	on water respon	se only; no shore	line protection feasible							
6	4-130.2	Morro Strand State Beach North/Willow Creek		100			2 small anchors or stakes			1-SSS	small anchors, stakes, or fence posts	2
6	4-135.2	Torro Creek		300			2					4
6	4-140.1	Morro Strand State Beach South	on water respon	se only; no shore	line protection feasible							
6	4-145.1	Morro Strand State Beach Pismo Clam Preserve	on water respon	se only; no shore	line protection feasible							
		7 24 hours	1000	600	6	4	6					16
18	4-120.1	Cayucos Point & San Geronimo Creek	on water respon	se only; no shore	line protection feasible			<u> </u>				
18	4-115.2	Villa Creek Inlet and Beach		300			2-small anchors or stakes			1-SSS		2
18	4-115.5	Villa Creek Inlet and Beach	on water respon	se only; no shore	line protection feasible	·						
18	4-120.1	Cayucos Point & San Geronimo Creek	on water respon	se only; no shore	line protection feasible							
18	4-120.3	Cayueos Point & San Geronimo Creek		100			2 small anchors or stakes			1-888		4
18	4-125.2	Cayucos Creek Inlet		200			2 small anchors or stakes			1-SSS		4
24	4-320.1	Diable Canyon Pwr Plant	1000)				2	2	SFS		6

		SHORELINE	PROT	ECTIO	ON TABLE	- SA	NTA BARBARA CHANI	NEL.	PT (CONCEPT	ON 8/2013	
Protect by hour	Strategy or Site	Site Name	Harbor Boom	Swamp Boom	Other Boom Amt Type	S orbent Boom	Anchoring Systems No. Kind	Boom Boats	Skiffs	Skimmers No. Type	Special Equipment and Notes	Staff
		First 6 hours	0	400	•	395	13			0		18
2	4-567.1	Pt. Conception/Government Pt.	on water respons	se only; no shorel	ine protection feasible							
4	4-570.1	Damsite Canyon Creek		100		80	5				1 FE Loader, 3 culvert, 2U sandbags, 1 u skakes, 1 roll plastic, 1 stake driver, 20' construction	n 5
4	4-572.1	San Augustine Creek				15					20 Sand Bags, 1 Roll Plastic, 3 Culverts, 15 Stakes, 1 hand tool	3
4	4-575.1	Arroyo El Bolito		100		100	4				1-FE Loader, 1-Roll Plastic, 3 Culverts, 20 Sand Bags, 15 Stakes, 1-stake driver, 10 construction fencing, 1 hand tool	9 5
5	4-580.1	Canada De Santa Anita (Creek)		200		200	4				1 FE Loader, 1 Roll Plastic, 3 Culverts, 20 Sand Bags, 15 Stakes, 1 stake driver, 10 construction fencing, 1 hand tool	¥ 5
		7-12 hours	0	800	0	800	12			0		15
8	4 585.1	Canada De Alegria		200		200	4				1 FE Loader, 1 Roll Plastie, 3 Culverts, 20 Sand Bags, 15 Stakes, 1 stake driver, 10 construction fencing, 1 hand tool	¥ 5
##	4 590.1	Canada Del Agua Caliente		200		200	4				1 FE Loader, 1 Roll Plastic, 3 Culverts, 20 Sand Bags, 15 Stakes, 1 stake driver, 10 construction fencing, 1 hand tool) ⁴ 5
##	4 601.1	Gaviota Creek		400		400	4				1 FE Loader, 1 Roll Plastic, 3 Culverts, 20 Sand Bags, 15 Stakes, 1 stake driver, 10 construction fencing, 1 hand tool	¥ 5
		13-24 hours	0	400	0	400	8			0		10
13	4 605.1	Canada Del Alcatraz & Cementario Cks					4				50 Sand Bags, 1 Roll Plastic, 3 Culverts, 1 hand tool	5
18	4 610.1	Refugio Creek		400		400	4				1 FE Loader, 1 Roll Plastic, 3 Culverts, 20 Sand Bags, 15 Stakes, 1 stake driver, 10 construction fencing, 1 hand tool	¥ 5

SHO	RELINE	PROTECTION TABLE - P	ORT	HUEN	EME REL	EASE	8/2013					
	Strategy or Sit Number		Harbor Boom	Swamp Boom	Other Boom Amt Type		Anchoring Systems No. Kind	Boom Boats	Skiffs	Skimmers No. Type	Special Equipment and Notes	Staff
•		First 6 hours	5400	0	0	2500	16			0		12
2	4-775.1	Channel Islands Harbor	3000			1500	8	2	2	1	(1) 20 yd waste bin, 1 portable oil storage tank	6
2	4-780.1	Port Hueneme	2400			1000	8	2	2	1	(1) 20 yd waste bin, 1 portable oil storage tank	6
		7 to 18 hours	2000	3000	0	3000	27			1		30
8	4-750.1	Santa Clara River Estuary		1500		1000	6				i i E loadei, i ion-plastic, 40 sand bags, 6 eulvei ts, 150 stakes, 3 stake drivers, 40 construction fencing, (1) 20 yd waste bin, 1 portable	10
9	4-747.1	Ventura Harbor	2000			1000	15	2	2	1	oil storage tank, 1 hand tool (1) 20 yd waste bin, 1 portable oil storage tank	10
10	4 783.1	Ormond Beach Wetlands & State Beach		1500		1000	6				1-FE loader, 1 roll plastie, 40 sand bags, 6 culverts, 150 stakes, 3 stake drivers, 40' construction fercine. (1) 20 vd waste bin. 1 portable	10
		19 - 24 hours	0	1000	0	1000	6			0		7
19	4 740.1	Ventura River Mouth		1000		1000	6		1		1 FE loader, 1 roll plastic, 40 sand bags, 6 culverts, 100 stakes, 3 stake drivers, 40' construction fencing. (1) 20 vd waste hin. 1 portable	9 7

\$ \$260.1 6 \$310.1 6 \$310.2	Site Name First 6 hours Alamitos Bay/Los Cerritos Wetlands Anaheim Bay (Seal Beach NWL Refuge) Anaheim Bay (Seal Beach NWL Refuge) 7-12 hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve Bolsa Chiea	Harbor Boom Swamp Boom S400 800 1500 3100 4200 2000 2000	Other Boom Ami Type	Serbent Boom 4		Beem Beats		Skimmers No. Type	Special Equipment and Notes On-water recovery/ART On-water recovery/ART	Si
5 5260.1 6 5310.1 6 5310.2 7 5230.1 7 5240.1 7 5250.1 8 5250.2	Alamitos Bay/Los Cerritos Wetlands Anaheim Bay (Seal Beach NWL Refuge) Anaheim Bay (Seal Beach NWL Refuge) 7—13-hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	800 1500 3100 4200 2000	n Amt Type	8 200	No. Kind 9 4 Dunforth 40lb 5 Dunforth 40lb 8	Beats		Skimmers No. Type	On water recovery/ART	<u>s</u>
\$ \$260.1 6 \$310.1 6 \$310.2 7 \$220.1 7 \$240.1 7 \$250.1 8 \$250.2	Alamitos Bay/Los Cerritos Wetlands Anaheim Bay (Seal Beach NWL Refuge) Anaheim Bay (Seal Beach NWL Refuge) 7—13-hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	\$400 800 1500 3100 4200 200	- "	298	4 Danforth 40lib 5 Danforth 40lib 00 8	+		No. Type	On water recovery/ART	<u> </u>
\$ \$260.1 6 \$310.1 6 \$310.2 7 \$230.1 7 \$240.1 7 \$250.1 8 \$250.2	Alamitos Bay/Los Cerritos Wetlands Anaheim Bay (Seal Beach NWL Refuge) Anaheim Bay (Seal Beach NWL Refuge) 7—13-hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	800 1500 3100 4200 200	a		4 Danforth 40lb 5 Danforth 40lb 8 8	1			· ·	
6 5310.1 6 5310.2 7 5220.1 7 5240.1 7 5250.1 8 5250.2	Ansheim Bay (Seal Beach NWL Refuge) Ansheim Bay (Seal Beach NWL Refuge) 7-12 hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	1500 3100 4200 200	0		5-Dunforth-40lb 8 8	1			· ·	
7 5230.1 7 5240.1 7 5250.1 8 5250.2	Anaheim Bay (Seal Beach NWL Refuge) 7–12 hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	3100 4300 2000	4		5-Dunforth-40lb 8 8	1			· ·	
7 \$ 230.1 7 \$ 240.1 7 \$ 250.1 8 \$ 250.2	7-12 hours Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	200 2000	4		90 8 90				· ·	
7 5-240.1 7 5-240.1 7 3-250.1 8 3-250.2	Middle Breakwater Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	200	4		00	1			· ·	
7 5-240.1 7 5-250.1 8 5-250.2	Long Beach Harbor Breakwater Golden Shore Marine Reserve Golden Shore Marine Reserve	2000		200		1			· ·	
7 5-250.1 8 5-250.2	Golden Shore Marine Reserve Golden Shore Marine Reserve	2000		200		1			On-water recovery/ARF	
§ 5-250.2	Golden Shore Marine Reserve Golden Shore Marine Reserve	2000		200		1				
•					4 Danforth 40lb	1				
12 5-320.1	Bolsa Chica									
	İ	2000			4 Danforth 40lb	1				
	13 – 24 hours	Δ.	4		4					
24 5-220.1	Los Angeles Harbor Breakwater								On water recovery/ART	
Strategy or Site Number	E PROTECTION TABLE		_)13				
		l [od P							
by hour	Site/Strategy Name	Harbor Swamp Boom Boom	Other Boom n Amt Type	Sorbent Boom	Anchoring Systems No. Kind	Boom Boots	Skiffs No	Skimmers No. Type	Special Equipment and Notes	Si
	Site/Strategy Name First 6 hours		Other Boom Amt Type		Anchoring Systems	Boom	Skiffs No	Skimmers No. Type	Special Equipment and Notes	Si
3 6400.6*	First 6 hours Shelter Island Deflection beom	Boom Boom 6000 3500	n Amt Type		Anchoring Systems	Boom		Skimmers No. Type	Special Equipment and Notes	<u>S</u>
3 6 400.6* 4 6 400.7*	First 6 hours Shelter Island Deflection boom North Island Collection boom	8000 Boom 6000 B	n Amt Type		Anchoring Systems No. Kind	Boom Boats		Skimmers No. Type	Special Equipment and Notes	<u>S</u>
3 6 400.6* 4 6 400.7*	First 6 hours Shelter Island Deflection beom	8000 Boom 6000 B	n Amt Type		Anchoring Systems No. Kind	Beem Beats		Skimmers No. Type	Special Equipment and Notes	\$
3 6-400.6± 1 4 6-400.7± 2000 ft of containment boom r	First 6 hours Shelter Island Deflection boom North Island Collection boom	8000 Boom 6000 B	n Amt Type	Boom	Anchoring Systems No. Kind	Beem Beats		Skimmers No. Type	Special Equipment and Notes	S-1
3 6 400.6* 4 6 400.7* 2000 ft of containment boom	First 6 hours Shelter Island Deflection boom North Island Collection boom n required to meet the 2 hour on-water containment requirement can be u 7—12-hours	Beem Beem	n Amt Type θ θ	Boom	Anchoring Systems No. Kind 12 S heavy anchor systems 4	Boom Beats		Skimmers No. Type	Special Equipment and Notes	S S
3 6-400.6± 1 4 6-400.7± 2000 ft of containment boom r	First 6 hours Shelter Island Deflection boom North Island Collection boom required to meet the 2 hour on-water containment requirement can be u	Boom Boom 6000 3500 2500 be utilized	n Amt Type θ θ	Boom	Anchoring Systems No. Kind 12 S heavy anchor systems 4	Beem Beats		Skimmers No. Type	Special Equipment and Notes	\$
3 6400.6° 4 6-00.7° 2000 ft of containment boom r 7 6-415.1 12 6-420.1	First 6 hours Shelter Island Deflection beom North Island Collection beom required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility	Beem Beem	n Amt Type θ θ	Beem	Anchoring Systems No. Kind 012 8 heavy anchor systems 4 011	Boom Boats		Skimmers No. Type	Special Equipment and Notes	5
3 6-400-62 4 6-400-72 2000 ft of containment boom r 7 6-415-1 12 6-420-1	First 6 hours Shelter Island Deflection boom North Island Collection boom n required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom	Beem Beem	n Ami Type e e	Beem	Anchoring Systems No. Kind 612 8 heavy anchor systems 4 611 3 8 med-weight anchor systems	Boom Boats		Skimmers No. Type	Special Equipment and Notes	\$
3 6-400-62 4 6-400-72 2000 ft of containment boom : 7 6-415-1 12 6-420-1	First 6 hours Shelter Island Deflection beom North Island Collection beom 1 required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours	Boom Boom	n Ami Type e e	Beem	Anchoring Systems No. Kind 12 Sheavy anchor systems 4 11. 3 S need weight anchor systems 0 28	Beem Beets		Skimmers No. Type	Special Equipment and Notes	\$
3 6-400-62 4 6-400-72 2000 ft of containment boom 1 7 6-415-1 12 6-420-1	First 6 hours Shelter Island Deflection beem North Island Collection beem n required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours USN Delta Beach	Boom Boom	n Ami Type e e	Beem	Anchoring Systems No. Kind 12 Sheavy anchor systems 4 11. 3 S need weight anchor systems 0 28	Beem Beets		Skimmers No. Type	Special Equipment and Notes	5
3 6400.6° 4 6-00.7° 2000 ft of containment boom r 7 6415.1 12 6420.1 16 6430.2 16 6440.2 24 6450.2	First 6 hours Shelter Island-Deflection-boom North Island Collection-boom North Island Collection-boom n required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours USN Delta Beach Paradise Marsh Sweetwater Kiver NWL Refuge Chula Vista Wildlife Reserve	Boom Boom	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	Beem	Anchoring Systems No. Kind 0 12 \$ heavy anchor systems 1 0 11 \$ med weight anchor systems 6 light wt anchor systems	Beem Bouts		Skimmers No. Type		\$
			Other Boom		Anchoring Systems	Boom	Ski	Skimmers		
3 6-400.6± 4 6-400.7± 2000 ft of containment boom r	First 6 hours Shelter Island Deflection boom North Island Collection boom n required to meet the 2 hour on-water containment requirement can be u 7—12-hours	Beem Beem	n Amt Type θ θ	Boom	Anchoring Systems No. Kind 12 S heavy anchor systems 4	Boom Beats		Skimmers No. Type	Special Equipment and Notes	
3 6-400-62 4 6-400-72 2000 ft of containment boom r	First 6 hours Shelter Island Deflection beom North Island Collection beom required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility	Boom Boom	n Amt Type θ θ	Boom	Anchoring Systems No. Kind 012 8 heavy anchor systems 4 011	Boom Boats		Skimmers No. Type	Special Equipment and Notes	<u>\$</u>
3 6-400.62 4 6-400.72 2000 ft of contament boom c	First 6 hours Shelter Island Deflection beom North Island Collection beom required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility	Boom Boom	n Amt Type θ θ	Boom	Anchoring Systems No. Kind 012 8 heavy anchor systems 4 011	Boom Boats		Skimmers No. Type	Special Equipment and Notes	\$
5 6 400.6 ² 6 400.7 ² 1000 R of containment boom r 6 415.1 2 6 420.1	First 6 hours Shelter Island Deflection boom North Island Collection boom n required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom	Beem Beem	n Ami Type e e	Beem	Anchoring Systems No. Kind 612 8 heavy anchor systems 4 611 3 8 med-weight anchor systems	Boom Boats		Skimmers No. Type	Special Equipment and Notes	\$
5 6 400.6 ² 6 400.7 ² 1000 R of containment boom r 6 415.1 2 6 420.1	First 6 hours Shelter Island Deflection boom North Island Collection boom n required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom	Beem Beem	n Ami Type e e	Beem	Anchoring Systems No. Kind 612 8 heavy anchor systems 4 611 3 8 med-weight anchor systems	Boom Boats		Skimmers No. Type	Special Equipment and Notes	S S
3 6-400.62 4 6-400.72 2000 ft of containment boom r 7 6-415.1 12 6-420.1	First 6 hours Shelter Island Deflection beom North Island Collection beom 1 required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours	Boom Boom	n Ami Type e e	Beem	Anchoring Systems No. Kind 12 Sheavy anchor systems 4 11. 3 S need weight anchor systems 0 28	Beem Beets		Skimmers No. Type	Special Equipment and Notes	\$
3 6-400-62 4 6-400-72 2000 ft of containment boom 1 7 6-415-1 12 6-420-1	First 6 hours Shelter Island Deflection beem North Island Collection beem n required to meet the 2 hour on water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours USN Delta Beach	Boom Boom	n Ami Type e e	Beem	Anchoring Systems No. Kind 12 Sheavy anchor systems 4 11. 3 S need weight anchor systems 0 28	Beem Beets		Skimmers No. Type	Special Equipment and Notes	\$
3 \$-400.62 4 \$-400.72 2000 ft of containment boom c 7 \$-415.1 12 \$-420.1 16 \$-430.2 16 \$-435.2	First 6-hours Shelter Island-Deflection boom North Island-Collection-boom n required to meet the 2-hour on-water containment requirement can be u 7—12-hours Navy-Magnetic Silencing Facility Cross Bay-Boom 13—24-hours USN Delta Beach Paradise Manh	Boom Boom	a a a 6786 a	Beem	Anchoring Systems No. Kind 0 12 \$ heavy anchor systems 1 0 11 \$ med weight anchor systems 6 light wt anchor systems	Beem Bouts		Skimmers No. Type	Special Equipment and Notes	\$
3 5-400.6º 4 6-400.7º 2000 ft of containment boom s 2 6-445.1 12 6-420.1 16 6-430.2 16 6-435.2 24 5-440.2	First 6 hours Shelter Island Deflection-boom North Island Collection-boom North Island Collection-boom required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours USN Delta Beach Paradrise March Sweetwater River NWLRefuge	Boom Boom	a a a 6786 a	Beem	Anchoring Systems No. Kind 12 3 heavy anchor systems 4 14 3 8 med weight anchor systems 6 light wt anchor systems 14 light wt anchor systems	Beem Beets 2 + 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2		Skimmers No. Type	Special Equipment and Notes	5
3 6-400.6º 4 6-400.7º 2000 ft of containment boom s 2 6-445.1 12 6-420.1 16 6-430.2 16 6-435.2 24 8-440.2	First 6 hours Shelter Island Deflection-boom North Island Collection-boom North Island Collection-boom required to meet the 2 hour on-water containment requirement can be u 7—12 hours Navy Magnetic Silencing Facility Cross Bay Boom 13—24 hours USN Delta Beach Paradrise March Sweetwater River NWLRefuge	Boom Boom	a a a 6786 a	Beem	Anchoring Systems No. Kind 12 3 heavy anchor systems 4 14 3 8 med weight anchor systems 6 light wt anchor systems 14 light wt anchor systems	Beem Beets 2 + 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2		Skimmers No. Type	Special Equipment and Notes Special Equipment and Notes Special Equipment and Notes	

		First 6 hours	10000	500	0	•	30				22
2	6-420.1*	Cross Bay Boom	2000				Q	2			4
3	6-430.2	USN Delta Beach	1500				6 light wt anchor systems	2			6
4	6-435.2	Paradise Marsh		500			1 light wt anchor systems	2			6
5		Sweetwater River NWLRefuge	6500				14 light wt anchor systems	2	-		6
D to 2000 ft	of containment boom	required to meet the 2 hour on-water containment requirement can be utilized									<u>. </u>
		7 12 hours	1500	0	0		8				23
7	6-455.2	South Bay NWL Refuge and Otay River	500				4 light wt anchor systems		1		4
Q	6-460.2	Emory Cove Marsh								300 sand bags, shovels and sand	15
10	6-400.10	Harbor Island Marina	1000				4 light wt anchor systems	1			4
		13 - 24 hours	3000	0	0		10				#
18	6.400.9	Commercial Basin	1000				4 light wt anchor systems	1			4
20	6-400.8	Shelter Island Marina	500				3 light wt anchor systems	1			4
24	6-415.1	Navy Magnetic Silenceinq Facility	1500			,	3 light wt anchor systems	1	·		3

Small Harbor BAP Shoreline Requirements for Small Vessel Response Plans 8/2013

		1	TOOL BALL SHOLE			1		1					
	deploy by	Strategy* or Site		Harbor Boom*	Swamp Boom*	Sorbent Boom*	Anchor Systems* No. Kind	Boom* Boats			kimmers .		
larbor	iloui	Number	Site Name / location						Skiffs		Турс	Special Equipment and Notes	Staff
Cresent City	3	as needed	Cresent City	1000		200	4 Danforth anchoring systems	4				oil sweep can be substituted for sorbent boom	3
Shelter Cove	3	as needed	Shelter Cove		1000	200	4 Danforth anchoring systems		4			oil sweep can be substituted for sorbent boom	3
ort Bragg	3	as needed	NoyoHarbor		1000	200	4 Danforth anchoring systems		4			oil sweep can be substituted for sorbent boom	3
Albion	3	as needed	Albion		1000	200	8 Danforth anchoring systems		4			oil sweep can be substituted for sorbent boom	3
Bodega Bay	3	2-118-2	Bodega Harbor	1800			1 22+ lb danforths	2				shoreside skimmer	8
	3	as needed	Bodega Harbor		1000	200	4 anchoring systems						
	-						g-,				l		
Bolinas	3	2-146.1	Bolinas Lagoon		3000	200	8 4x12+# anchors + 4 stakes		3				
Pillar Point	3	2-162.4	Pillar Point Marsh & Denniston Creek	500			9 2/50+ & 7/22 danforths + chains	4	4				
	3	as needed	Pillar Point Marsh & Denniston Creek		1000	200	4 anchoring systems						
	7	2-162.4	Pillar Point Marsh & Denniston Creek							1	SPS		
Santa Cruz													
	3	3-220.1	Santa Cruz Harbor Entrance	2500			7 Danforth anchoring systems	3			SPS	skimmer with 3 staff	11
	7	3-210.1	San Lorenzo River Inlet		800	400	9 Danforth anchoring systems				SSS	600' 6" PVC pipe or berm	20
Mana Landina					1000	200	4 Danifarith analysmin a sustains		4				3
Moss Landing	3	as needed		1		200	4 Danforth anchoring systems	+	4		-		
	7	3-305.1	Moss Landing Inlet	5500	1600	2000 OS	1 7 Stakes & 3 Danforth	4		3	SSS	Share VSW boom boats + Elkhorn Slough crew.	20
	7	3-310.1	Elkhorn Slough		6000	12000 OS	8 4 Stakes & 4 Danforth as needed	2				Remark: backup to Moss Landing - one or more chevrons. VSW boomboat	10
Morro Bay	3	4-200.2	Morro Bay Inlet	2000			2 40 lb. Anchors	2		1	SES		6
mono suy	7	4-225.1	Chorro Creek Inlet	=		50	2 small anchors or stakes			1 SS		fence posts	4
	7	4-230.1	Los Osos Creek Inlet			50	2 small anchors or stakes			1 SS		terice posis	4
	7.	4-235.2	Sweet Springs Marsh		300		2 small anchors or stakes			1 SS	e .	fence posts	4
	7	4-240.1	Cuesta by the Sea Inlet		200		2 small anchors or stakes			1 SS		terice posis	4
Port San Luis / Avilla	3	4-335	Port San Luis / Avilla	on-water response	200		4 dividio di otando			1 00		on-water response only; no shoreline protection feasible	
	3	4-665.1	Santa Barbara Harbor	4000		2500							
Santa Barbara Harbor	7			4000	0		2 anchoring systems	2	4	4		(1) 20 yd waste bin, 1 portable oil storage tank	10
	7	4-670.2 4-672.2	Mission Creek / Laguna Channel Sycamore Creek and Andre Clark Bird R	Refuge	1600 400	1600 400	8 anchoring systems					160 stakes, 2 stake drivers, (1) 4wd vehicle 160 stakes, 2 stake drivers, (1) 4wd vehicle	8
	+	4-072.2	ayeamore Greek and Andre Glark Bird K	Reluge	400	400	₈ anchoring systems					160 Stakes, 2 Stake univers, (1) 4wa venicie	8
Ventura Harbor	3	4-747.1	Ventura Harbor	2000		1000	4 anchoring systems	2	2	4		(1) 20 yd waste bin, 1 portable oil storage tank	10
												1 FE loader, 1 roll plastic, 6 culverts, 40 sand bags,	
	3	4-750.1	Santa Clara River estuary		1500	1000	6 anchoring systems		4			150 stakes, 3 stake drivers, 40' construction fencing, (1) 20 yd waste bin, 1 portable eil storage tank, 1	10
Channel Islands Harbor	3	4-775.1	Channel Islands Harbor	3000		1500	8 anchoring systems	2	2			(1) 20 yd waste bin, 1 portable oil storage tank	6
Marina Del Rey	3	as needed	Marina Del Rey		1000	200		1					3
warina bei Key		as needed	warina Del Key		1000	200	3 anchoring systems	+					3
	3												
	•	5-140.1	Ballona Creek	500			1 40 lb Danforth anchoring systems	4					4
	3	5-140.1 5-150.1	Ballona Creek Ballona Lagoon Wetlands	500			1 40 lb Danforth-anchoring-systems	4				Close Tidal Gates.	4
				500			1 40 lb Danforth-anchoring-systems	4				Close Tidal Gates. Block Culvert. Sandbags/Inflatable Plug	4
Kjn^Harbor	3	5-150.1	Ballona Lagoon Wetlands	500	1000	200	4 anchoring systems 4 anchoring systems	4	4				3
	3	5-150.2 as needed as needed	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor	500	1000 1000	200		4	4			Block-CulvertSandbags/Inflatable-Plug	
	3 3	5-150.1 5-150.2 as needed	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or	500			4 anchoring systems	4	4				3
Dana Point	3 3 3 3	5-150.2 as needed as needed 5-390.2	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor San Juan Creek				4 anchoring systems 4 anchoring systems		4			Block-CulvertSandbags/Inflatable-Plug	3
Dana Point	3 3 3	5-150.2 as needed as needed	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor	2000			4 anchoring systems	7	4			Block-CulvertSandbags/Inflatable-Plug	3
Dana Point Newport Bay Harbor	3 3 3 3 7	5-150.2 as-needed as-needed 5-390.2 5-360.4 5-365.1	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor San Juan Creek Lower Ne^port_Bay Upper Newpe^Bay		1000		4-anchoring systems 4-anchoring systems 5-anchoring systems 4-anchorin^ystems		4			Block-CulvertSandbags/Inflatable-Plug	3 10 4
Dana Point Newport Bay Harbor	3 3 3 3 3 7	5-150.2 as-needed as-needed 5-390.2 5-360.1 5-365.4 as-needed	Ballona Lageen Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor San Juan Creek Lower Ne^port_Bay Upper Newpo^Bay Oceanside & Carlebad harbors	2000 1000			4 anchoring systems 4 anchoring systems 5 anchoring systems	7 4	4			Block-CulvertSandbags/Inflatable-Plug	3 10 4 4
Dana Point Newport Bay Harbor	3 3 3 3 7	5-150.2 as-needed as-needed 5-390.2 5-360.4 5-365.1	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor San Juan Creek Lower Ne^port_Bay Upper Newpe^Bay	2000	1000		4-anchoring systems 4-anchoring systems 5-anchoring systems 4-anchorin^ystems	7	4			Block-CulvertSandbags/Inflatable-Plug	3 10 4
Dana Point Newport Bay Harbor Decanside/Carlsbad	3 3 3 3 3 7	5-150.2 as-needed as-needed 5-390.2 5-360.1 5-365.4 as-needed	Ballona Lageen Wetlands Ballona Wetlands Kin^Ha^er Dana Point Harber San Juan Creek Lower Ne^port_Bay Upper Newpe^Bay Oceanside & Carlebad harbers Santa Margarita River	2000 1000	1000		4 anchoring systems 4 anchoring systems 5 anchoring systems 4 anchorin^ystems 4 anchoring systems	7 4	4			Block-CulvertSandbags/Inflatable-Plug	3 10 4 4
Dana Point Newport Bay Harbor Decanside/Carlsbad	3 3 3 3 3 7	5-150.2 as needed as needed 5-390.2 5-360.1 6-365.1 as needed 6-145.2	Ballona Lagoon Wetlands Ballona Wetlands Kin^Ha^or Dana Point Harbor San Juan Creek Lewer Ne^port_Bay Upper Newpo^Bay Oceanside & Carlebad harbors Santa Margarita River Mission Bay entrance	2000 1000 3000	1000		4 anchoring systems 4 anchoring systems 5 anchoring systems 4 anchorin^ystems 4 anchoring systems 8 anchorin^systems	7 4	4			Block-CulvertSandbags/Inflatable-Plug	3 10 4 4 8
Kjn^Harber Dana Point Newport Bay Harber Oceanside/Carlsbad	3 3 3 3 3 7	5-150.2 ss needed ss needed 6-390.2 5-360.1 5-365.1 ss needed 6-145.2 6-200.1	Ballona Lageen Wetlands Ballona Wetlands Kin^Ha^er Dana Point Harber San Juan Creek Lower Ne^port_Bay Upper Newpe^Bay Oceanside & Carlebad harbers Santa Margarita River	2000 4000 3000 800	1000		4 anchoring systems 4 anchoring systems 5 anchoring systems 4 anchoring systems 4 anchoring systems 8 anchoring systems 2 anchoring systems	7 4	4			Block-CulvertSandbags/Inflatable-Plug	3 40 4 4 8

REPEAL

Glossary of Terms Used in the BAP Shoreline Protection Tables

August 29, 2013

Anchoring Systems - Anchoring systems refer to anchors, stakes and other devices necessary to secure booms and other mechanically deployed protection measures. When used to identify anchors, whether expressly stated or not, anchoring systems must be sufficient to hold boom in the aggressive currents such as are common to SF Bay and other California estuaries. Typically systems are presented as a number of anchors and minimal weight (e.g., 3/12+ - means three anchors of a minimum of 12 lbs each) with at least an equal weight of anchor chain weight whether specified or not; without substantial anchor chain weight, anchors will not hold. To insure successful anchoring, the anchoring system should include: anchors with anchor buoys to control placement, anchor chains which equal or exceed the weight of anchors, enough line to produce adequate scope to hold anchors (rule of thumb is 3:1 (line to depth), but 5-7:1 for high current areas), and a crown buoy between anchor line and boom to keep the anchor from sinking the boom under strong currents.

BBoat - see Boom Boat

Boom Boats - a boat suitable for transporting, towing and deploying large amounts of boom, usually crewed with a helmsman and two crew for deployment. Numbers of such boats usually are referenced in terms of boom boat equivalent (BBE). BBE is the capability of a vessel to transport and deploy 600 feet of Harbor Boom or 1800 ft of Swamp Boom. Actual vessels may be capable of transporting greater or lesser amounts of boom. Boom boats must be capable of grounding without sustaining damage. (Also see Shallow Water Boom Boats and Very Shallow Water Boom Boats.)

Danforth - refers to "danforth anchors" with chain. Northill anchors and other anchor types which "dig in" are equivalent.

FELoader - Front-end-loader or skip-loader: mechanical equipment with mechanical scoop or bucket for moving sediment.

GNOME - General NOAA Oil Spill Modeling Environment

Harbor Boom - an inland waters type boom (greater than 18" and less than 42" overall (flotation and skirt)) of a curtain boom design (skirted boom with solid flotation). Early strategies attempted to clarify boom size by indicating flotation and skirt as follows: 9X9+ which indicated a boom with at least 9" of flotation and 9" of skirt, and would now be interpreted as at least 18" overall. This boom type typically has strength members (steel cable and chain) in both upper and lower margins.

Protect By Hour—the hour after the release when the site must be protected to insure that the site protection is in place before the oil is likely to impact. Generally, this time is about an hour prior to impact, but may be otherwise due to uncertainty of impact time.

Other Boom—is any boom other than harbor boom, swamp boom, or sorbent boom. This term is used to simplify equipment tables. A type designator should be used as well as a length. Type designators include: **TB** or TBB - tidal barrier boom or Texas barrier boom **OB** - ocean boom **OS** - oil snare

SWEP - oil sweep: sorbent pads in continuous strips Shallow Water - less than three feet of water Shallow Water Boom Boats - a boom boat capable of working in three feet of water or less, and should be able to withstand stranding without sustaining damage.

Skiff - a small two person craft able to operate in 3 foot waves or larger and capable of delivering personnel and equipment to shores.

Skimmer refers to a skimming system. A skimming system includes a collection device (such as a weir, ropemop, drum, or other skimming design to separate oil from the aqueous environment), storage for collected material, power supply to power such a system, and all the hoses and connectors necessary for system operation. Types of skimmers refer to the configuration of the deployment of such systems rather than a particular device or manufacturer.

SFS - stationary floating skimmer - a floating platform supporting a skimmer and storage.

SPS - self-propelled skimmer - a small to medium sized skimmer with its own propulsion and storage.

SSS shore side skimmer, includes a skimming unit, such as a rope mop or weir skimmer and its support pack and a storage container such as a vacuum truck, baker tank, or other tank.

SWS - Shallow Water Skimmers - Skimmers capable of operating in less than two feet of water.

Towed Skimming Array - a skimming system with two boats towing collection booms connected to a skimmer (in a "V" formation) to funnel oil to the skimmer and may be referred to with the acronyms TSA and VSA.

TSA - (towed skimming array as above) - a skimming array with two boats towing collection booms which funnel oil to a skimming system, of either SPS or SFS design.

VSA - "V"-Skimming Array -Same as TSA

OSRV - Oil Spill Response Vessel. A large **self-powered** vessel dedicated to oil spill skimming and response **VOSS** - Vessel of Opportunity Skimming System - Usually moderate to large vessel which can be equipped

with a skimming device and storage to create a mobile on water skimmer capable of operating in local conditions and waters.

Sorbent Boom - sorbents in a boom or sausage-like construction with or without a skirt.

Strategy or Site Number - deployments are listed in the Area Contingency Plan by a site number or as a strategy number which includes the site number.

Swamp Boom - a river boom type (less than 18" overall, usually less than 12" overall) of a curtain boom design. Usually this boom has much lighter strength members, commonly only a single chain in the skirt. This boom is suitable for modest currents and locations without waves.

VSW - very shallow water

Very Shallow Water - less than two feet of water

Very Shallow Water Boom Boats - a boom boat capable of working in two feet of water or less, and should be able to withstand stranding without sustaining damage.