

SINTERFIRE, INC.

200 Industrial Park Road
 Kersey, PA 15846
 Phone: (814) 885-6672

Website: www.sinterfire.com

Projectile Designation	Caliber(s)	Grain(s)	% lead content by weight	Unique Identifying Characteristics
SF12-325 RHSS**	12 ga	325	< 1%	Hollow base; flat nose
SF00-35 RHBS**	12 ga	35	< 1%	Belt around mid-section
SF9-100-NXG	9mm	100	< 1%	Flat Point
SF45-70-300 RHVF**	.45	300	< 1%	Concave point
SF45-155 RHHP**	.45	155	< 1%	Concave or hollow point
SF223-50-NXG	.223	50	< 1%	Wide Taper Point
SF223-55 WTP**	.223	55	< 1%	Wide Taper Point
SF308-125 NTP**	.30	125	< 1%	Narrow Taper Point
SF7.62x39-123 NTP**	.310	123	< 1%	Narrow Taper Point
SF223-45 WTP**	.223	45	< 1%	Wide Taper Point Nose
SF223-42 WTP**	.223	42	< 1%	Wide Taper Point Nose
SF223-55 FMJ**	.223	55	< 1%	Very small hole in nose
SF110-300 Blackout**	.308	110	< 1%	Narrow Taper Point
.380 Auto	.380	70	< 1%	Flat Point-Black Nylon Coating
9mm	.355	90	< 1%	Flat Point-Black Nylon Coating
40 S&W	.400	115	< 1%	Flat Point-Black Nylon Coating
45 Aut	.451	140	< 1%	Flat Point-Black Nylon Coating
10mm Auto	.400	115	< 1%	Flat Point-Black Nylon Coating
SF380-75 FeN	.380	70	< 1%	Flat Point-Black Nylon Coating
SF9-90 FeN	.355	90	< 1%	Flat Point-Black Nylon Coating
SF40-115 FeN	.400	115	< 1%	Flat Point-Black Nylon Coating

SF45-140 FeN	.451	140	< 1%	Flat Point-Black Nylon Coating
SF10-115 FeN	.400	115	< 1%	Flat Point-Black Nylon Coating

**** Frangible bullets are certified for use on appropriate non-game species only**