

STREAM INVENTORY REPORT

Abalobadiah Creek

WATERSHED OVERVIEW

Abalobadiah Creek is a tributary to the Pacific Ocean (Figure 1). Elevations range from 0 feet at the mouth of the creek to 800 feet in the headwater areas. Abalobadiah Creek's legal description at the confluence with the Pacific Ocean is T20N R17W S28. Its location is 39°34'16"N. Latitude and 123°45'39"W. Longitude according to the USGS Inglenook 7.5 minute quadrangle. Abalobadiah Creek drains a watershed of approximately 1,955 acres.

HABITAT INVENTORY RESULTS

The habitat inventory of August 21 through October 8, 1996, was conducted by Dave Wright and Diana Hines. The total length of surveyed stream in Abalobadiah Creek was 10,548 feet (2.0 miles, 3.2 km) (Table 1). There were no side channels in this creek.

Flow measured at the mouth of Abalobadiah Creek on October 17, 1996 was 1.5 cubic feet per second (cfs).

Abalobadiah Creek consists of one reach which included the entire mainstem survey.

Table 1 summarizes the Level II riffle, flatwater and pool habitat types. By percentage occurrence, riffles comprised 20%, flatwater 42% and pools 36% of the habitat types (Graph 1). By percent total length, riffles comprised 19%, flatwater 59% and pools 19% (Graph 2).

Sixteen Level IV habitat types were identified and are summarized in Table 2. The most frequently occurring habitat types were low gradient riffles, 20%, step runs, 17%, and glides, 16% (Graph 3). The most prevalent habitat types by percent total length were step runs at 35%, low gradient riffles at 19% and glides at 16% (Table 2).

Table 3 summarizes main, scour and backwater pools which are Level III pool habitat types. Scour pools were most often encountered at 71% occurrence and comprised 72% of the total length of pools.

Table 4 is a summary of maximum pool depths by Level IV pool habitat types. In second order streams, pools with depths of two feet (0.61 m) or greater are considered optimal for fish habitat. In Abalobadiah Creek, seven of the 89 pools (8%) had a depth of two feet or greater (Graph 4).

The depth of cobble embeddedness was estimated at pool tail-outs. Of the pool tail-outs measured, 0% had a value of 1, 0% had a value of 2, 10% had a value of 3 and 90% had a value of 4 (Graph 5).

Abalobadiah Creek

Of the Level II habitat types, pools had the highest mean shelter rating at 29 (Table 1). Of the Level III pool habitat types, scour pools had the highest mean shelter rating at 38 (Table 3).

Of the 89 pools, 50% were formed by large woody debris : 17% by logs and 23% by root wads (calculated from Table 4).

Table 6 summarizes dominant substrate by Level IV habitat types. Of the low gradient riffles fully measured, 25% had gravel as the dominant substrate (Graph 6).

Mean percent closed canopy was 82%: 23% coniferous trees and 59% deciduous trees. Mean percent open canopy was 18% (Graph 7, calculated from Table 7).

Table 7 summarizes the mean percent substrate and vegetation types found along the banks of the stream. Mean percent right bank vegetated was 68% while mean percent left bank vegetated was 62%. Deciduous Trees were the dominant bank vegetation type in 35% of the units fully measured. The dominant substrate composing the structure of the stream banks was sand/silt/clay, found in 59% of the units fully measured.

DISCUSSION

The information gathered in the process of habitat typing will provide Georgia-Pacific with baseline data on the current condition of this creek and the available habitat for salmonids. These data can be used to identify components of the habitat in need of enhancement so appropriate conditions for Abalobadiah Creek can be obtained over time.

Level II habitat types by percent occurrence and length

Flatwater habitat types comprised a high percentage of the units by both percent occurrence and length at 42% and 59% respectively (Table 1 and Graph 1). These unit types usually do not provide optimal spawning or rearing habitat for salmonids. Riffle habitat units comprised a moderate percentage of the stream by both percent occurrence and length at 20% and 19% respectively. Pools also comprised a moderate percentage by both percent occurrence and length at 36% and 19% respectively. Riffles usually provide good spawning habitat while pools provide important rearing habitat. In addition, Mundie (1969) reported that invertebrate food production is maximized in riffles while pools provide an optimum feeding environment for coho salmon. In fact, the most productive streams are those consisting of a pool to riffle ratio of approximately one to one (Ruggles 1966).

Pool Depth

According to Flosi and Reynolds (1994), a stream with at least 50% of its total habitat comprised of primary pools is generally desirable. Primary pools are at least two feet deep in first and second order streams and at least three feet deep in third order streams. The information from Graph 4 (maximum depth in pools) was used to determine percent of primary pools.

Abalobadiah Creek

Abalobadiah Creek, a second order stream, is comprised mainly of shallow pools with only 8% of the pools having a maximum depth of two feet or greater.

Instream Shelter

Instream shelter ratings are derived from two measurements: instream shelter complexity and instream shelter percent cover. The first is a value rating which provides a relative measure of the quality and composition of the shelter; the second is a measure of the area of a habitat unit covered by shelter. The various types of instream shelter include LWD, small woody debris, boulders, root wads, terrestrial vegetation, aquatic vegetation, bedrock ledges and undercut banks. Of the Level II habitat types, Pools had the highest shelter rating at 29. Of the Level III habitat types Scour Pools had the highest shelter rating at 38. These values are low as shelter values of 80 or higher are considered optimum for good rearing habitat (Flosi and Reynolds 1994).

Large Woody Debris

The presence of large woody debris (LWD) in streams is a significant component of fish habitat. Woody debris creates areas of low flow, providing a refuge for fish during periods of high flow (Robison and Beschta, 1990). Woody debris also provides cover for fish, lowering the risk of predation. The percent of pools formed by LWD in Abalobadiah Creek was 50%. Whether these numbers are high or low, relative to the needs of salmonids is difficult to ascertain since the optimum amount of woody debris in streams has not been specified (Robison and Beschta 1990). However, based on data from Georgia-Pacific's 1995 Aquatic Vertebrate Study, the only coho found in the Ten Mile River Basin were in stream reaches where approximately 50% of pools were formed by large woody debris. Those reaches that did not support coho had a significantly lower percentage of pools formed by large woody debris (Ambrose et al, 1996). This suggests that a low percentage of LWD formed pools could adversely affect juvenile coho populations (C.S. Shirvel 1990).

The above LWD analysis pertains only to pools formed by logs or root wads as described in Flosi and Reynolds (1994): lateral scour pool-log enhanced, lateral scour pool-rootwad enhanced, backwater pool-log formed and backwater pool-rootwad formed. Other pools containing LWD as a component were not included in the calculation. For example, plunge pools may be formed by boulders, bedrock or LWD, but are not described as such by habitat unit types. Therefore, the LWD formed pool calculation is limited to four pool types and does not quantify the total amount of LWD in Abalobadiah Creek.

Canopy

There are two important benefits of canopy cover in coastal streams. Canopy keeps stream temperatures cool as well as providing nutrients such as leaf litter and organic material (Bilby 1988). This leaf litter, organic material, and their associated nutrients are utilized as a food source by benthic macroinvertebrates (aquatic insects). The macroinvertebrates, in turn, are major food sources for most fish species in forested areas (Gregory et al., 1987). Mean percent

Abalobadiah Creek

canopy cover for the Abalobadiah Creek was 82%. This is relatively high since a canopy cover of 80% or higher is considered optimum (Flosi and Reynolds, 1994).

Deciduous trees occupied a larger portion of the canopy than did coniferous trees. Coniferous trees comprised only 23% of the canopy. Wood from alders and most other deciduous species deteriorates more rapidly than wood from coniferous species (Sedell, *et al.* 1988). Therefore, less LWD would be available for future fish cover and LWD formed pools in Abalobadiah creek, as well as other creeks dominated by deciduous species.

Embeddedness

High embeddedness values (silt levels), such as those found in Abalobadiah creek, have been associated with many negative impacts to salmonids. These negative impacts can be observed in important environmental components of salmonid habitat, such as pool habitats, dissolved oxygen levels and water temperatures.

The impact high silt levels have on pool habitat is that they fill in and eventually eliminate pools. As already mentioned, pools provide important habitat for rearing salmonids.

High silt levels also impact oxygen levels in the water. They do so by reducing water circulation within the substrate, thus lowering the oxygen levels needed by salmonid eggs (Sandercock, 1991). This can hinder the survival of the eggs deposited in redds, as well as the survival of juvenile salmonids.

Water temperature is impacted by high silt levels in several ways. Hagans et al (1986) reported the following impacts to water temperatures: 1) the loss of a reflective bottom; 2) darker sediment (as opposed to clean gravels) storing heat from direct solar radiation which is then transferred to the water column; and 3) a reduction in the flow of water through the substrate interstitial spaces, thereby exposing more of the water column to direct solar radiation.

Another means by which water temperatures are increased is through the widening of stream channels: over time, high silt levels increase the substrate surface level of the creek, resulting in a wider, shallower stream channel (Flosi and Reynolds, 1994). In shallow streams more surface area is exposed to the sun relative to the volume of water, leading to an increase in solar heating which in turn leads to higher water temperatures.

Substrates embedded with silt in varying degrees were given corresponding values as follows: 0-25%= value 1, 26 - 50% = value 2, 51 - 75% = value 3 and 76 - 100% = value 4. According to Flosi and Reynolds (1994), creeks with embeddedness values of two or higher are considered to have poor quality fish habitat. In the Abalobadiah Creek, 100% of the pool tail-outs measured had embeddedness values of two or more.

It is important to consider, however, that the above embeddedness values were obtained in the summer during low flow conditions. In winter and spring, flows are usually higher due to the rainy season and the lowered evapotranspiration of the trees. This higher flow can carry away

Abalobadiah Creek

some of the previously deposited silt to sites further downstream. Therefore, embeddedness values may fluctuate throughout the year along different sections of the stream.

Substrate

In Abalobadiah Creek, 25% of the low gradient riffles had gravel as the dominant substrate. Small cobble was not present in any of the riffles surveyed. The relatively low presence of gravel and the absence of small cobble in riffles indicates that there is an insufficient amount of substrate available as potential spawning habitat in this creek.

It is also important to note that 63% of the low gradient riffles surveyed were dominated by sand. The high degree of sand and silt observed most likely occurred due to cattle, which were observed to be freely ranging throughout the creek. While the cattle appeared to occur mainly on property not owned by Georgia Pacific (the lower section of creek), due to lack of fencing, there was evidence of cattle roaming onto G.P. lands.

It is important to consider is that regardless of the amount of substrate or spawning habitat available, this habitat may not be suitable for salmonids if it is highly embedded.

Overall, Abalobadiah Creek appears to have low shelter values, high embeddedness values and insufficient substrate for spawning. While the canopy closure was adequate in volume, it was deficient in composition: It contained a relatively low amount of conifers. The creek did possess an adequate amount of LWD formed pools, unfortunately the amount of primary pools, overall, was extremely low. The paucity of primary pools is most likely due to the erosional effects of unrestrained cattle in areas of the creek not owned by Georgia Pacific.

Georgia-Pacific recognizes that there are areas of the mainstem Abalobadiah Creek in need of enhancement, and where feasible will attempt to restore those areas over time as part of its long term management plan. The company will also attempt to facilitate a healthy environment for salmonids in this creek through sound management practices.

RECOMMENDATIONS

- 1) Efforts should be made to remove cattle from G.P. owned section of Abalobadiah Creek, such as the maintenance and construction of fencing.
- 2) Abalobadiah Creek should be managed as an anadromous, natural production watershed.
- 3) Where feasible, design and engineer pool enhancement structures to increase the depth of pools. This must be done where the banks are stable or in conjunction with stream bank armor to prevent erosion.
- 4) Shelter values throughout Abalobadiah Creek could be increased by addition of large logs and root wads, boulder clusters, log and boulder weirs and log and boulder deflectors. These need to be placed carefully to prevent washing out in high flows. The

Abalobadiah Creek

Stream Habitat Restoration Manual, by Flosi and Reynolds, 1994, provide detailed descriptions for restoration efforts.

- 5) Log debris accumulations retaining large quantities of fine sediment should be modified if necessary, over time, to avoid excessive sediment loading in downstream reaches.
- 6) Sources of stream bank erosion should be mapped and prioritized according to present and potential sediment yield. Identified sites should then be treated to reduce the amount of fine sediment entering the stream. In addition, sediment sources related to road systems need to be identified, mapped and treated according to their potential for sediment yield to the watershed.
- 7) Spawning gravel in this creek was limited. Projects should be designed at suitable sites to trap spawning gravel in order to increase spawning habitat throughout the stream.

COMMENTS AND LANDMARKS

The following landmarks and possible problem sites were noted. All distances are approximate and taken from the beginning of the survey reach.

Position
(ft):

Comments:

557	Cattle appear to be unrestrained throughout the riparian area. Cow patties and cow trails can be found in almost all areas. Two 40 mm steelhead observed.
589	Eight 50 mm steelhead observed.
772	Approximately 15 salmonids observed.
1382	Fifteen steelhead observed.
1967	Road crossing a (see enclosed map).
2025	Thirty salmonids observed.
2225	Approximately 12 salmonids observed.
3184	Road crossing and confluence with East Branch Abalobadiah Creek.
3975	Road crossing.
4561	Hobo temperature monitor in pool.
5514	Approximately 15 salmonids observed.

Abalobadiah Creek

- 5829 Confluence with West Branch Abalobadiah Creek.
- 7301 Approximately 10 salmonids observed.
- 8238 Confluence with Gulch One.
- 8394 After confluence with Gulch One, the creek changed to a conifer dominated area.
- 8403 Six 35 mm steelhead observed.
- 9338 Confluence with Gulch 3. Gulch 3 is dry.
- 9529 Log jam measures 10' x 15' x 30'. Possible barrier to anadromy.
- 10290 Large log jam measures 50' long x20' wide x 15' high.
- 10548 End of survey due to diminished habitat.

Abalobadiah Creek

