

STREAM INVENTORY REPORT

Rider Gulch

WATERSHED OVERVIEW

Rider Gulch is a tributary to Wages Creek (Figure 1). Elevations range from 100 feet at the mouth of the creek to 600 feet in the headwater areas. Rider Gulch's legal description at the confluence with Wages Creek is T21N R17W Sec29. Its location is 39°38'18"N. latitude and 123°46'15"W. longitude according to the USGS Westport 7.5 minute quadrangle.

HABITAT INVENTORY RESULTS

The habitat inventory of September 5, 1996 through September 10, 1996, was conducted by Diana Hines and Dave Wright. The total length of surveyed stream in Rider Gulch was 8290 feet (1.6 miles, 2.5 KM) (Table 1). There were no side channels in this creek.

Flow measured at the mouth of Rider Gulch on September 12, 1996 was 0.07 cubic feet per second (cfs).

Rider Gulch consists of one reach: An F4 for the entire 8,290 feet of creek.

Table 1 summarizes the Level II riffle, flatwater and pool habitat types. By percent occurrence, riffles comprised 12%, flatwater 41% and pools 45% of the habitat types (Graph 1). By percent total length, riffles comprised 8%, flatwater 72% and pools 19% (Graph 2).

Ten Level IV habitat types were identified and are summarized in Table 2. The most frequently occurring habitat types were step runs 33%, mid-channel pools 21%, and low gradient riffles 12% (Graph 3). The most prevalent habitat types by percent total length were step runs at 66% and low gradient riffles and mid-channel pools, both at 8% (Table 2).

Table 3 summarizes main, scour and backwater pools which are Level III pool habitat types. Scour pools were most often encountered at 53% occurrence and comprised 57% of the total length of pools.

Table 4 is a summary of maximum pool depths by Level IV pool habitat types. In second order streams, pools with depths of two feet (0.61 m) or greater are considered optimal for fish habitat. In Rider Gulch, 15 of the 73 pools (21%) had a depth of two feet or greater (Graph 4).

The depth of cobble embeddedness was estimated at pool tail-outs. Of the pool tail-outs measured, 0% had a value of 1, 0% had a value of 2, 0% had a value of 3 and 100% had a value of 4 (Graph 5).

Rider Gulch

Of the Level II habitat types, both flatwater and pools habitat types had the highest mean shelter ratings at 12 each (Table 1). Of the Level III pool habitat types, scour pools had the highest mean shelter rating at 13 (Table 3).

Of the 73 pools, 29% were formed by large woody debris (LWD): 22% by logs and 7% by root wads (calculated from Table 4).

Table 6 summarizes dominant substrate by Level IV habitat types. Of the low gradient riffles fully measured, 100% had gravel as the dominant substrate (Graph 6).

Mean percent closed canopy was 98%: 42% coniferous trees and 56% deciduous trees. Mean percent open canopy was 2% (Graph 7, calculated from Table 7).

Table 7 summarizes the mean percent substrate/vegetation types found along the banks of the stream. Mean percent right bank vegetated was 90% while mean percent left bank vegetated was 84%. Deciduous trees were the dominant bank vegetation type in 46% of the units fully measured. The dominant substrate composing the structure of the stream banks was cobble/gravel, found in 61% of the units fully measured.

DISCUSSION

The information gathered in the process of habitat typing will provide Georgia-Pacific with baseline data on the current condition of this creek and the available habitat for salmonids. These data can be used to identify components of the habitat which are in need of enhancement so appropriate conditions for Rider Gulch can be obtained over time.

Level II habitat types by percent occurrence and length

Flatwater habitat types comprised a high percentage of the units by both percent occurrence and length at 41% and 72% respectively (Table 1 and Graph 1). These unit types usually do not provide optimal spawning or rearing habitat for salmonids. Riffle habitat units comprised a low percentage of the stream by both percent occurrence and length at 12% and 8% respectively. Pools, however, comprised a higher percentage by both percent occurrence and length at 45% and 19% respectively. Riffles usually provide good spawning habitat while pools provide important rearing habitat. In addition, Mundie (1969) reported that invertebrate food production is maximized in riffles while pools provide an optimum feeding environment for coho. In fact, the most productive streams are those consisting of a pool to riffle ratio of approximately one to one (Ruggles 1966).

Pool Depth

According to Flosi and Reynolds (1994), a stream with at least 50% of its total habitat comprised of primary pools is generally desirable. Primary pools are at least two feet deep in first and second order streams and at least three feet deep in third order streams. The information from

Rider Gulch

Graph 4 on maximum depth in pools was used to determine percent of primary pools. Rider Gulch, a second order stream, is comprised mainly of shallow pools with 21% of the pools having a maximum depth of two feet or greater.

Instream Shelter

Instream shelter ratings are derived from two measurements: instream shelter complexity and instream shelter percent cover. The first is a value rating which provides a relative measure of the quality and composition of the shelter, and the second is a measure of the area of a habitat unit covered by shelter. The various types of instream shelter include LWD, small woody debris, boulders, rootwads, terrestrial vegetation, aquatic vegetation, bedrock ledges and undercut banks. Of the Level II habitat types both Flatwater units and Pools had the highest shelter ratings at 12 each. Of the Level III habitat types Scour Pools had the highest shelter rating at 53. These values are low as shelter values of 80 or higher are considered optimal for good rearing habitat (Flosi and Reynolds 1994).

Large Woody Debris

The presence of large woody debris in streams is a significant component of fish habitat. Woody debris creates areas of low flow, providing a refuge for fish during periods of high flow (Robison and Beschta, 1990). Woody debris also provides cover for fish, lowering the risk of predation. The percent of pools formed by LWD in Rider Gulch was 29%. Whether these numbers are high or low, relative to the needs of salmonids is difficult to ascertain since the optimum amount of woody debris in streams has not been specified (Robison and Beschta 1990). However, based on data from Georgia-Pacific's 1995 Aquatic Vertebrate Study, the only coho salmon found in the Ten Mile River Basin were in stream reaches where approximately 50% of pools were formed by large woody debris. Those reaches that did not support coho had a significantly lower percentage of pools formed by large woody debris (Ambrose et al, 1996). This suggests that a low percentage of LWD formed pools could adversely affect juvenile coho populations (C.S. Shirvel 1990).

The above LWD analysis pertains only to pools formed by logs or root wads as described in Flosi and Reynolds (1994): lateral scour pool-log enhanced, lateral scour pool-rootwad enhanced, backwater pool-log formed and backwater pool-rootwad formed. Other pools containing LWD as a component were not included in the calculation. For example, plunge pools may be formed by boulders, bedrock or LWD but are not described as such by habitat unit types. Therefore, the LWD formed pool calculation is limited to four pool types and does not quantify the amount of LWD in Rider Gulch.

Canopy

There are two important benefits of canopy cover in coastal streams. Canopy keeps stream temperatures cool as well as providing nutrients in the form of leaf litter and organic material (Bilby 1988). This leaf litter, organic material, and their associated nutrients are utilized as a food source by benthic macroinvertebrates (aquatic insects). The macroinvertebrates, in turn, are major food sources for most fish species in forested areas (Gregory et al., 1987). Mean percent

Rider Gulch

canopy cover for the Rider Gulch was 98%. This is high since a canopy cover of 80% or higher is considered optimum (Flosi and Reynolds, 1994).

Deciduous trees occupied a slightly larger portion of the canopy than did coniferous trees. Deciduous trees comprised 56% and coniferous trees 42% of the canopy. The significance of this is that wood from alder and most other deciduous species deteriorates more rapidly than wood from coniferous species (Sedell, *et al.* 1988). Therefore, less LWD would be available in the future for fish cover and LWD formed pools in this creek and others dominated by deciduous species.

Embeddedness

High embeddedness values (silt levels), such as those found in Rider Gulch, have been associated with many negative impacts to salmonids. These negative impacts can be observed in important environmental components of salmonid habitat, such as pool habitats, dissolved oxygen levels and water temperatures.

The impact high silt levels have on pool habitat is that they fill in and eventually eliminate pools. As already mentioned, pools provide important habitat for rearing salmonids.

High silt levels also impact oxygen levels in the water. They do so by reducing water circulation within the substrate, thus lowering the oxygen levels needed by salmonid eggs (Sandercock, 1991). This can hinder the survival of the eggs deposited in redds, as well as the survival of juvenile salmonids.

Water temperature is impacted by high silt levels in several ways. Hagans et al (1986) reported the following impacts to water temperatures: 1) the loss of a reflective bottom; 2) darker sediment (as opposed to clean gravels) storing heat from direct solar radiation which is then transferred to the water column; and 3) a reduction in the flow of water through the substrate interstitial spaces thereby exposing more of the water column to direct solar radiation.

Another means by which water temperatures are increased is through the widening of stream channels: over time, high silt levels increase the substrate surface level of the creek, resulting in a wider, shallower stream channel (Flosi and Reynolds, 1994). In shallow streams more surface area is exposed to the sun relative to the volume of water, leading to an increase in solar heating which in turn leads to higher water temperatures.

Substrates embedded with silt in varying degrees were given corresponding values as follows: 0-25%= value 1, 26 - 50% = value 2, 51 - 75% = value 3 and 76 - 100% = value 4. According to Flosi and Reynolds (1994), creeks with embeddedness values of two or higher are considered to have poor quality fish habitat. In Rider Gulch, 100% of the pool tail-outs measured had embeddedness values of two or more.

It is important to consider, however, that the above embeddedness values were obtained in the summer during low flow conditions. In winter and spring, flows are usually higher due to the rainy season and the lowered evapotranspiration of the trees. This higher flow can carry away

Rider Gulch

some of the previously deposited silt to sites further downstream. Therefore, embeddedness values may fluctuate throughout the year along different sections of the stream.

Substrate

In Rider Gulch, 100% of the low gradient riffles had gravel as the dominant substrate. The relatively high concentration of gravel in riffles indicates that there is a sufficient amount of substrate available as potential spawning habitat in this creek. While this creek had sufficient substrate for spawning in the riffles surveyed, the overall percentage of riffles in the surveyed portions of the creek was very low at only 12 (Table 1). Subsequently, there may be a lack of sufficient spawning habitat. Another point to consider is that regardless of the amount of substrate or spawning habitat available, this habitat may not be suitable for salmonids if it is highly embedded.

Overall, Rider Gulch appears to have a relatively and high percentage of LWD formed pools and sufficient canopy. However, this stream also appears to have a low percentage of primary pools, low shelter values and high embeddedness values. In addition, while there was sufficient substrate for spawning, habitat for spawning appeared to be limited.

Georgia-Pacific recognizes that there are areas of Rider Gulch in need of enhancement, and where feasible will attempt to restore those areas over time as part of its long term management plan. The company will also attempt to facilitate a healthy environment for salmonids in this creek through sound management practices.

RECOMMENDATIONS

- 1) Rider Gulch should be managed as an anadromous, natural production watershed.
- 2) Where feasible, design and engineer pool enhancement structures to increase the depth of pools. This must be done where the banks are stable or in conjunction with stream bank armor to prevent erosion.
- 3) Shelter values throughout Rider Gulch could be increased by addition of large logs and root wads, boulder clusters, log and boulder wiers and log and boulder deflectors. These need to be placed carefully to prevent washing out in high flows. The Stream Habitat Restoration Manual, by Flosi and Reynolds, 1994, provides detailed descriptions for restoration efforts.
- 4) Log debris accumulations retaining large quantities of fine sediment should be modified if necessary, over time, to avoid excessive sediment loading in downstream reaches.
- 5) Sources of stream bank erosion should be mapped and prioritized according to present and potential sediment yield. Identified sites should then be treated to reduce the amount of fine sediment entering the stream. In addition, sediment sources related to road

Rider Gulch

systems need to be identified, mapped and treated according to their potential for sediment yield to the watershed.

COMMENTS AND LANDMARKS

The following landmarks and possible problem sites were noted. All distances are approximate and taken from the beginning of the survey reach.

Position (ft):	Comments:
30	Approximately thirty salmonids observed (3 inches).
662	No fish observed (NFO) since first pool.
1845	Three young-of-the-year (YOY) salmonids observed - approximately two inches long.
2221	Tributary entering on the left bank, not accessible to fish (NAF).
2254	Channel type is an F4.
3714	Bridge.
3883	NFO for about last 30 units.
4827	Tributary entering on right bank. NAF.
5037	Bridge crossing.
5340	Culvert entering on right bank. NAF. Log jam measures 10' long x 8' wide x 2' high.
5490	Tributary entering through culvert on right bank at 38'. NAF.
5726	Bridge.
5784	Two large redwoods fallen over creek.
6055	Three YOY observed, approx. two inches long.
6340	Tributary enters on left bank.
8290	End of survey due to diminished habitat. Very little flow after confluence with left bank tributary.

Rider Gulch

