## STREAM INVENTORY REPORT

#### Minon Creek

## **INTRODUCTION**

A stream inventory was conducted during the summer of 2001 on Minon Creek. The survey began at the confluence with Redwood Creek and extended upstream 1.2 miles.

The Minon Creek inventory was conducted in two parts: habitat inventory and biological inventory. The objective of the habitat inventory was to document the habitat available to anadromous salmonids in Minon Creek. The objective of the biological inventory was to document the presence and distribution of juvenile salmonid species.

The objective of this report is to document the current habitat conditions and recommend options for the potential enhancement of habitat for coho salmon and steelhead trout. Recommendations for habitat improvement activities are based upon target habitat values suitable for salmonids in California's north coast streams.

## WATERSHED OVERVIEW

Minon Creek is a tributary to the Redwood Creek, which drains to the Pacific Ocean. It is located in Humboldt County, California (Map 1). Minon Creek's legal description at the confluence with Redwood Creek is T05N R04E S20. Its location is 41.8067 degrees north latitude and 123.7479 degrees west longitude. Minon Creek is a first order stream and has approximately 3.1 miles of blue line stream according to the USGS Grouse Mountain 7.5 minute quadrangle. Minon Creek drains a watershed of approximately 4.2 square miles. Elevations range from about 1,400 feet at the mouth of the creek to 4,850 feet in the headwater areas. Redwood forest, Douglas fir forest and grassland dominate the watershed. The watershed is entirely privately owned and is managed for rangeland and timber production. Vehicle access exists via Bald Mountain Road to Snow Camp Road to Guy Kerr Road.

## **METHODS**

The habitat inventory conducted in Minon Creek follows the methodology presented in the *California Salmonid Stream Habitat Restoration Manual* (Flosi et al, 1998). The California Conservation Corps (CCC) Technical Advisors and Watershed Stewards Project/AmeriCorps (WSP/AmeriCorps) Members that conducted the inventory were trained in standardized habitat inventory methods by the California Department of Fish and Game (DFG). This inventory was conducted by a two-person team.

## SAMPLING STRATEGY

The inventory uses a method that samples approximately 10% of the habitat units within the survey reach. All habitat units included in the survey are classified according to habitat type and their lengths are measured. All pool units are measured for maximum depth, depth of pool tail crest (measured in the thalweg), dominant substrate composing the pool tail crest, and embeddedness. Habitat unit types encountered for the first time are measured for all the parameters and characteristics on the field form. Additionally, from the ten habitat units on each field form page, one is randomly selected for complete measurement.

## HABITAT INVENTORY COMPONENTS

A standardized habitat inventory form has been developed for use in California stream surveys and can be found in the *California Salmonid Stream Habitat Restoration Manual*. This form was used in Minon Creek to record measurements and observations. There are nine components to the inventory form.

#### 1. Flow:

Flow is measured in cubic feet per second (cfs) at the bottom of the stream survey reach using a Marsh-McBirney Model 2000 flow meter.

# 2. Channel Type:

Channel typing is conducted according to the classification system developed and revised by David Rosgen (1985 rev. 1994). This methodology is described in the *California Salmonid Stream Habitat Restoration Manual*. Channel typing is conducted simultaneously with habitat typing and follows a standard form to record measurements and observations. There are five measured parameters used to determine channel type: 1) water slope gradient, 2) entrenchment, 3) width/depth ratio, 4) substrate composition, and 5) sinuosity. Channel characteristics are measured using a clinometer, hand level, hip chain, tape measure, and a stadia rod.

## 3. Temperatures:

Both water and air temperatures are measured and recorded at every tenth habitat unit. The time of the measurement is also recorded. Both temperatures are taken in degrees Fahrenheit at the middle of the habitat unit and within one foot of the water surface.

## 4. Habitat Type:

Habitat typing uses the 24 habitat classification types defined by McCain and others (1988). Habitat units are numbered sequentially and assigned a type identification number selected from a standard list of 24 habitat types. Dewatered units are labeled "dry". Minon Creek habitat typing used standard basin level measurement criteria. These parameters require that the minimum length of a described habitat unit must be equal to or greater than the stream's mean

wetted width. All measurements are in feet to the nearest tenth. Habitat characteristics are measured using a clinometer, hip chain, and stadia rod.

#### 5. Embeddedness:

The depth of embeddedness of the cobbles in pool tail-out areas is measured by the percent of the cobble that is surrounded or buried by fine sediment. In Minon Creek, embeddedness was ocularly estimated. The values were recorded using the following ranges: 0 - 25% (value 1), 26 - 50% (value 2), 51 - 75% (value 3) and 76 - 100% (value 4). Additionally, a value of 5 was assigned to tail-outs deemed not suitable for spawning due to inappropriate substrate particle size, bedrock, or other considerations.

## 6. Shelter Rating:

Instream shelter is composed of those elements within a stream channel that provide salmonids protection from predation, reduce water velocities so fish can rest and conserve energy, and allow separation of territorial units to reduce density related competition. The shelter rating is calculated for each fully-described habitat unit by multiplying shelter value and percent cover. Using an overhead view, a quantitative estimate of the percentage of the habitat unit covered is made. All cover is then classified according to a list of nine cover types. In Minon Creek, a standard qualitative shelter value of 0 (none), 1 (low), 2 (medium), or 3 (high) was assigned according to the complexity of the cover. Thus, shelter ratings can range from 0-300 and are expressed as mean values by habitat types within a stream.

## 7. Substrate Composition:

Substrate composition ranges from silt/clay sized particles to boulders and bedrock elements. In all fully-described habitat units, dominant and sub-dominant substrate elements were ocularly estimated using a list of seven size classes and recorded as a one and two, respectively. In addition, the dominant substrate composing the pool tail-outs is recorded for each pool.

## 8. Canopy:

Stream canopy density was estimated using modified handheld spherical densiometers as described in the *California Salmonid Stream Habitat Restoration Manual*. Canopy density relates to the amount of stream shaded from the sun. In Minon Creek, an estimate of the percentage of the habitat unit covered by canopy was made from the center of approximately every third unit in addition to every fully-described unit, giving an approximate 30% sub-sample. In addition, the area of canopy was estimated ocularly into percentages of coniferous or deciduous trees.

## 9. Bank Composition and Vegetation:

Bank composition elements range from bedrock to bare soil. However, the stream banks are usually covered with grass, brush, or trees. These factors influence the ability of stream banks to withstand winter flows. In Minon Creek, the dominant composition type and the dominant

vegetation type of both the right and left banks for each fully-described unit were selected from the habitat inventory form. Additionally, the percent of each bank covered by vegetation (including downed trees, logs, and rootwads) was estimated and recorded.

## **BIOLOGICAL INVENTORY**

Biological sampling during the stream inventory is used to determine fish species and their distribution in the stream. Fish presence was observed from the stream banks in Minon Creek. In addition, twelve sites were electrofished using a Smith-Root Model 12 electrofisher. These sampling techniques are discussed in the *California Salmonid Stream Habitat Restoration Manual*.

## DATA ANALYSIS

Data from the habitat inventory form are entered into Habitat, a dBASE 4.2 data entry program developed by Tim Curtis, Inland Fisheries Division, California Department of Fish and Game. This program processes and summarizes the data, and produces the following six tables:

- Riffle, flatwater, and pool habitat types
- Habitat types and measured parameters
- Pool types
- Maximum pool depths by habitat types
- Dominant substrates by habitat types
- Mean percent shelter by habitat types

Graphics are produced from the tables using Quattro Pro. Graphics developed for Minon Creek include:

- Riffle, flatwater, pool habitats by percent occurrence
- Riffle, flatwater, pool habitats by total length
- Total habitat types by percent occurrence
- Pool types by percent occurrence
- Total pools by maximum depths
- Embeddedness
- Pool cover by cover type
- Dominant substrate in low gradient riffles
- Mean percent canopy
- Bank composition by composition type
- Bank vegetation by vegetation type

## HABITAT INVENTORY RESULTS

The habitat inventory of October 22 through October 24, 2001 was conducted by D. Best (CCC) and D. Resnik (WSP). The total length of the stream surveyed was 6,179 feet with an additional 616 feet of side channel.

Stream flow was not measured on Minon Creek.

Minon Creek is an F4 channel type for the first 1,101 feet, a B2 channel type for 1,784 feet, and an F2 channel type for 3,294 feet of the stream channel. Channels types classified as "F" are entrenched, meandering, riffle/pool channels on low gradients with high width/depth ratios. F4 channels are gravel dominated and F2 channels are boulder dominated. B2 channels are moderately entrenched, moderate gradient, riffle dominated channel with infrequently spaced pools, very stable plan and profile, stable banks, and boulder dominated channel.

Water temperatures taken during the survey period ranged from 48 to 52 degrees Fahrenheit. Air temperatures ranged from 50 to 62 degrees Fahrenheit.

Table 1 summarizes the Level II riffle, flatwater, and pool habitat types. Based on frequency of occurrence there were 35% flatwater units, 34% pool units, and 27% riffle units (Graph 1). Based on total length of Level II habitat types there were 52% flatwater units, 22% riffle units, and 17% pool units (Graph 2).

Twelve Level IV habitat types were identified (Table 2). The most frequent habitat types by percent occurrence were step runs, 26%; low gradient riffles, 17%; and mid-channel pools, 13% (Graph 3). Based on percent total length, step runs made up 47%, low gradient riffles, 13%, and high gradient riffles 9%.

A total of 47 pools were identified (Table 3). Main channel pools were the most frequently encountered, at 47%, and comprised 58% of the total length of all pools (Graph 4).

Table 4 is a summary of maximum pool depths by pool habitat types. Pool quality for salmonids increases with depth. Eighteen of the forty-seven pools (38%) had a depth of two feet or greater (Graph 5).

The depth of cobble embeddedness was estimated at pool tail-outs. Of the 47 pool tail-outs measured, 15 had a value of 1 (32%); 15 had a value of 2 (32%); 13 had a value of 3 (13%); one had a value of 4 (2%); and 10 had a value of 5 (21%); (Graph 6). On this scale, a value of 1 indicates the highest quality of spawning substrate. The breakdown of dominant substrate composition for the 10 pool tail-outs that had an embeddedness value of 5 were as follows: nine with boulders and one with bedrock.

A shelter rating was calculated for each habitat unit and expressed as a mean value for each habitat type within the survey using a scale of 0-300. Riffle habitat types had a mean shelter rating of 24, flatwater habitat types had a mean shelter rating of 12, and pool habitats had a mean shelter rating of 25 (Table 1). Of the pool types, the backwater pools had the highest mean

shelter rating at 65. Main channel pools had a mean shelter rating of 22 (Table 3).

Table 5 summarizes mean percent cover by habitat type. Boulders are the dominant cover types in Minon Creek. Graph 7 describes the pool cover in Minon Creek. Boulders are the dominant pool cover type followed by whitewater.

Table 6 summarizes the dominant substrate by habitat type. Graph 8 depicts the dominant substrate observed in pool tail-outs. Gravel was the dominant substrate observed in 51% of pool tail-outs while boulder was the next most frequently observed substrate type, at 19%.

The mean percent canopy density for the surveyed length of Minon Creek was 90%. The mean percentages of deciduous and coniferous trees were 82% and 18%, respectively. Graph 9 describes the mean percent canopy in Minon Creek.

For the stream reach surveyed, the mean percent right bank vegetated was 73%. The mean percent left bank vegetated was 77%. The dominant elements composing the structure of the stream banks consisted of 53% cobble/gravel, 26% boulders, 14% sand/silt/clay, and 8% bedrock (Graph 10). Deciduous trees were the dominant vegetation type observed in 73% of the units surveyed. Additionally, 18% of the units surveyed had coniferous trees as the dominant vegetation type, and 9% had brush as the dominant vegetation (Graph 11).

## BIOLOGICAL INVENTORY RESULTS

Twelve sites were electrofished for species composition and distribution in Minon Creek on October 29, 2001. Water temperatures taken during the electrofishing period ranged from 51 to 52 degrees Fahrenheit. Air temperatures ranged from 54 to 58 degrees Fahrenheit. The sites were sampled by T. Tollefson (DFG), D. Best (CCC), and D. Resnik (WSP/AmeriCorps).

The first site sampled was habitat unit 006, a lateral scour pool approximately 230 feet from the confluence with Redwood Creek. The site yielded 7 young-of-the-year, and 2 age one-plus steelhead.

The second site was habitat unit 009, a mid-channel pool located approximately 360 feet above the creek mouth. The site yielded 3 young-of-the-year and 1 age one-plus steelhead.

The third site sampled was habitat unit 012, a mid-channel pool located approximately 510 feet above the creek mouth. The site yielded 8 young-of-the-year and 2 age one-plus steelhead.

The fourth site sampled was habitat unit 014, a lateral scour pool - boulder formed located approximately 580 feet above the creek mouth. The site yielded 6 young-of-the-year and 6 age one-plus steelhead.

The fifth site sampled was habitat unit 017, a lateral scour pool - bedrock formed located approximately 735 feet above the creek mouth. The site yielded 1 young-of-the-year, 2 age one-plus, and 1 age two-plus steelhead.

The sixth site sampled was habitat unit 020, a mid-channel pool located approximately 895 feet above the creek mouth. The site yielded 17 young-of-the-year, and 5 age one-plus steelhead.

The seventh site sampled was habitat unit 033, a plunge pool located approximately 1,506 feet above the creek mouth. The site yielded 2 young-of-the-year steelhead.

The eighth site sampled was habitat units 039, a mid-channel pool located approximately 1,717 feet above the creek mouth. The site yielded 4 young-of-the-year and 3 age one-plus steelhead.

The ninth site sampled was habitat unit 044, a plunge pool located approximately 1,839 feet above the creek mouth. The site yielded 4 young-of-the-year and 2 age one-plus steelhead.

The tenth site sampled was habitat unit 052, a step pool located approximately 2,267 feet above the creek mouth. The site yielded 8 young-of-the-year and 2 age one-plus steelhead.

The eleventh site sampled was habitat unit 060, a plunge pool located approximately 2,638 feet above the creek mouth. The site yielded 9 young-of-the-year, 5 age one-plus, and 1 age two-plus steelhead.

The twelfth site sampled was habitat unit 066, a plunge pool located approximately 2,911 feet above the creek mouth. The site yielded 4 young-of-the-year and 4 age one-plus steelhead.

The following chart displays the information yielded from these sites:

Date	Site #	Approx. Dist. from mouth (ft.)	Hab. Unit #	Hab. Type	Reach #	Channel type		teelhe OY 1+	
10/29/01	1	230	0006	5.2	1	F4	7	2	0
10/29/01	2	360	0009	4.2	1	F4	3	1	0
10/29/01	3	510	0012	4.2	1	F4	8	2	0
10/29/01	4	580	0014	5.5	1	F4	6	6	0
10/29/01	5	735	0017	5.4	1	F4	1	2	1
10/29/01	6	895	0020	4.2	2	B2	17	5	0
10/29/01	7	1,506	0033	5.6	2	B2	2	0	0
10/29/01	8	1,717	0039	4.2	2	B2	4	3	0

Date	Site #	Approx. Dist. from mouth (ft.)	Hab. Unit #	Hab. Type	Reach #	Channel type		teelhe OY 1+	
10/29/01	9	1,839	0044	5.6	2	B2	4	2	0
10/29/01	10	2,267	0052	4.4	2	B2	8	2	0
10/29/01	11	2,638	0060	5.6	2	B2	9	5	1
10/29/01	12	2,911	0066	5.6	3	F2	4	4	0

## **DISCUSSION**

Minon Creek is a F4 channel type for the first 1,101 feet of stream surveyed and a B2 channel type for 1,784 feet and a F2 channel type for the remaining 3,294 feet of the stream surveyed. The suitability of F4 channel types for fish habitat improvement structures is as follows: good for bank placed boulders, fair for plunge weirs, single and opposing wing-deflectors, channel constrictors, log cover; poor for boulder clusters. The suitability of B2 channel types for fish habitat improvement structures is: excellent for log cover. The suitability of F2 channel types is: fair for plunge weirs, single and opposing wing deflectors and log cover.

The water temperatures recorded on the survey days October 22-24, 2001, ranged from 50 to 52 degrees Fahrenheit. Air temperatures ranged from 50 to 62 degrees Fahrenheit. This is a good water temperature range for salmonids. To make any further conclusions, temperatures would need to be monitored throughout the warm summer months, and more extensive biological sampling would need to be conducted.

Flatwater habitat types comprised 52% of the total **length** of this survey, riffles 22%, and pools 17%. The pools are relatively shallow, with 18 of the 47 (38%) pools having a maximum depth greater than 2 feet. In general, pool enhancement projects are considered when primary pools comprise less than 40% of the length of total stream habitat. In first and second order streams, a primary pool is defined to have a maximum depth of at least two feet, occupy at least half the width of the low flow channel, and be as long as the low flow channel width.

Thirty of the 47 pool tail-outs measured had embeddedness ratings of 1 or 2. Seven of the pool tail-outs had embeddedness ratings of 3 or 4. Ten of the pool tail-outs had a rating of 5, which is considered unsuitable for spawning. Nine of the ten were unsuitable for spawning due to the dominant substrate being boulder. The other pool tail valued at 5 was dominated by bedrock. Cobble embeddedness measured to be 25% or less, a rating of 1, is considered to indicate good quality spawning substrate for salmon and steelhead.

Thirty-one of the 47 pool tail-outs measured had gravel or small cobble as the dominant substrate. This is generally considered good for spawning salmonids.

The mean shelter rating for pools was 25. The shelter rating in the flatwater habitats was 12. A pool shelter rating of approximately 100 is desirable. The relatively small amount of cover that now exists is being provided primarily by boulders in all habitat types. Additionally, whitewater contributes a small amount. Log and root wad cover structures in the pool and flatwater habitats would enhance both summer and winter salmonid habitat. Log cover structure provides rearing fry with protection from predation, rest from water velocity, and also divides territorial units to reduce density related competition.

The mean percent canopy density for the stream was 90%. Reach 1 had a canopy density of 83% while Reaches 2 and 3 had canopy densities of 90% and 92%, respectively. In general, revegetation projects are considered when canopy density is less than 80% or the canopy composition is dominated by deciduous trees. The percentage of right and left bank covered with vegetation was 73% and 77%, respectively.

## **RECOMMENDATIONS**

- 1) Minon Creek should be managed as an anadromous, natural production stream.
- 2) The limited water temperature data available suggest that maximum temperatures are within the acceptable range for juvenile salmonids. To establish more complete and meaningful temperature regime information, 24-hour monitoring during the July and August temperature extreme period should be performed for 3 to 5 years.
- 3) Increase woody cover in the pools and flatwater habitat units. Most of the existing cover is from boulders. Adding high quality complexity with woody cover is desirable.
- 4) In the F4 channel type design and engineer pool enhancement structures to increase the number of pools or deepen existing pools. This must be done where the banks are stable or in conjunction with stream bank armor to prevent erosion.
- Increase the canopy on Minon Creek by planting redwood, Douglas fir or other native conifers within the riparian zone. Tributaries to Minon Creek and the reaches above this survey section should be inventoried and treated as well, since the water flowing here is effected from upstream.

# **COMMENTS AND LANDMARKS**

The following landmarks and possible problem sites were noted. All distances are approximate and taken from the beginning of the survey reach.

Position (ft):	Comments:
0'	Start of survey at the confluence with Redwood Creek. The channel type is F4.
230'	Electrofishing site #1.
360'	Electrofishing site #2.
433'	Erosion site on the left bank measures approximately 150' high x 80' long.
510'	Electrofishing site #3.
580'	Electrofishing site #4.
735'	Electrofishing site #5.
895'	Electrofishing site #6.
1,101'	Channel type changes from F4 to B2.
1,506'	Electrofishing site #7.
1,717'	Electrofishing site #8.
1,839'	Electrofishing site #9.
1,978'	Channel type changes from B2 to F2.
2,267'	Electrofishing site #10.
2,638'	Electrofishing site #11.
2,911'	Electrofishing site #12.
5,680'	Erosion site on the left bank measures approximately 60' high x 20' long.
6,179'	End of Survey. The last 500' of survey was a series of cascades with few resting pools. No fish seen for several habitat units. The channel continues to steepen and get more confined above endpoint.

# **REFERENCES**

Flosi, G., Downie, S., Hopelain, J., Bird, M., Coey, R., and Collins, B. 1998. *California Salmonid Stream Habitat Restoration Manual*, 3rd edition. California Department of Fish and Game, Sacramento, California.

# **LEVEL III and LEVEL IV HABITAT TYPES**

RIFFLE			
Low Gradient Riffle	(LGR)	[1.1]	{ 1}
High Gradient Riffle	(HGR)	[1.2]	{ 2}
CASCADE			
Cascade	(CAS)	[2.1]	{ 3}
Bedrock Sheet	(BRS)	[2.2]	{24}
	,	2	,
FLATWATER			
Pocket Water	(POW)	[3.1]	{21}
Glide	(GLD)	[3.2]	{14}
Run	(RUN)	[3.3]	{15}
Step Run	(SRN)	[3.4]	{16}
Edgewater	(EDW)	[3.5]	{18}
MAIN CHANNEL POOLS			
Trench Pool	(TRP)	[4.1]	{ 8 }
Mid-Channel Pool	(MCP)	[4.2]	{17}
Channel Confluence Pool	(CCP)	[4.3]	{19}
Step Pool	(STP)	[4.4]	{23}
SCOUR POOLS	(CDD)	F. 7. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	(22)
Corner Pool	(CRP)	[5.1]	{22}
Lateral Scour Pool - Log Enhanced	(LSL)	[5.2]	{10}
Lateral Scour Pool - Root Wad Enhanced	(LSR)	[5.3]	{11}
Lateral Scour Pool - Bedrock Formed	(LSBk)	[5.4]	{12}
Lateral Scour Pool - Boulder Formed	(LSBo)	[5.5]	{20}
Plunge Pool	(PLP)	[5.6]	{ 9}
BACKWATER POOLS			
Secondary Channel Pool	(SCP)	[6.1]	{ 4}
Backwater Pool - Boulder Formed	(BPB)	[6.2]	{ 5}
Backwater Pool - Root Wad Formed	(BPR)	[6.3]	{ 6}
Backwater Pool - Log Formed	(BPL)	[6.4]	{ 7}
Dammed Pool	(DPL)	[6.5]	{13}
ADDITIONAL UNIT DESIGNATIONS			
Dry	(DRY)	[7.0]	
Culvert	(CUL)	[8.0]	
Not Surveyed	(NS)	[9.0]	
Not Surveyed due to a marsh	(MAR)	[9.1]	
1.00 201 to jou and to a maintain	(2,21,21)	[/14]	